


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**737101**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0114595</b>	PCA0105297	PCA0100788
Sample Date	Client Info		<b>16 Jan 2024</b>	05 Sep 2023	27 Jul 2023
Machine Age	mls	Client Info	<b>71105</b>	201081	51471
Oil Age	mls	Client Info	<b>71105</b>	201081	51471
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>54</b>	87	58
Chromium	ppm	ASTM D5185m >20	<b>2</b>	4	3
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	1	<1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	2	1
Silver	ppm	ASTM D5185m >3	<b>0</b>	<1	0
Aluminum	ppm	ASTM D5185m >20	<b>16</b>	37	32
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m >330	<b>16</b>	48	42
Tin	ppm	ASTM D5185m >15	<b>1</b>	2	1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>2</b>	4	3
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	2
Molybdenum	ppm	ASTM D5185m 50	<b>60</b>	66	59
Manganese	ppm	ASTM D5185m 0	<b>1</b>	2	1
Magnesium	ppm	ASTM D5185m 950	<b>885</b>	941	865
Calcium	ppm	ASTM D5185m 1050	<b>1249</b>	1389	1292
Phosphorus	ppm	ASTM D5185m 995	<b>1005</b>	1063	979
Zinc	ppm	ASTM D5185m 1180	<b>1221</b>	1345	1215
Sulfur	ppm	ASTM D5185m 2600	<b>2073</b>	2725	2290

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>10</b>	9	7
Sodium	ppm	ASTM D5185m	<b>3</b>	3	2
Potassium	ppm	ASTM D5185m >20	<b>32</b>	81	64



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1.5</b>	1.8	1.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>14.7</b>	16.9	13.8
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>27.0</b>	29.2	25.9

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>27.8</b>	33.6	27.2
Base Number (BN)	mg KOH/g	ASTM D2896	<b>3.7</b>	3.6	4.5









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.9	12.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0114595 **Recieved** : 26 Jan 2024  
**Lab Number** : 06071380 **Diagnosed** : 30 Jan 2024  
**Unique Number** : 10848057 **Diagnostician** : Sean Felton  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #118**  
 2196 BENNETT ROAD  
 PHILADELPHIA, PA  
 US 19116  
 Contact: ROSTY VITER  
 rviter@millertransgroup.com  
 T: (215)552-9832  
 F: (215)552-9892

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)