




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**(41-028)**  
 Machine Id  
**227020-9991**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0045463</b>	GFL0101339	GFL0091820
Sample Date	Client Info	<b>23 Jan 2024</b>	28 Dec 2023	10 Oct 2023
Machine Age	mls	<b>284548</b>	3610	3161
Oil Age	mls	<b>133117</b>	0	0
Oil Changed	Client Info	<b>Changed</b>	Not Changd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>13</b>	9	16
Chromium	ppm ASTM D5185m >20	<b>0</b>	1	0
Nickel	ppm ASTM D5185m >4	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>2</b>	2	3
Lead	ppm ASTM D5185m >40	<b>10</b>	0	19
Copper	ppm ASTM D5185m >330	<b>&lt;1</b>	0	1
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	0	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>6</b>	0	<1
Barium	ppm ASTM D5185m 0	<b>0</b>	4	0
Molybdenum	ppm ASTM D5185m 60	<b>64</b>	61	64
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	0	0
Magnesium	ppm ASTM D5185m 1010	<b>1054</b>	942	1019
Calcium	ppm ASTM D5185m 1070	<b>1168</b>	1065	1155
Phosphorus	ppm ASTM D5185m 1150	<b>1059</b>	1064	1046
Zinc	ppm ASTM D5185m 1270	<b>1317</b>	1228	1336
Sulfur	ppm ASTM D5185m 2060	<b>3052</b>	3393	2932

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>6</b>	1	9
Sodium	ppm ASTM D5185m	<b>3</b>	0	3
Potassium	ppm ASTM D5185m >20	<b>0</b>	3	<1

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>1.4</b>	0.9	1.4
Nitration	Abs/cm *ASTM D7624 >20	<b>12.6</b>	10.3	12.2
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>23.5</b>	20.6	23.2

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>21.1</b>	18.2	20.2
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.9</b>	8.4	7.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.4</b>	13.4	13.8

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0045463 **Received** : 26 Jan 2024  
**Lab Number** : **06072157** **Diagnosed** : 29 Jan 2024  
**Unique Number** : 10848834 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 654 - Richmond Hauling**  
 11800 Lewis Road  
 Chester, VA  
 US 23831  
 Contact: Jimmy Mayes  
 jmayes@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)