


OIL ANALYSIS REPORT



GFL035 834038 Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (42 QTS)





DIAGNOSIS

Recommendation

The oil is near the end of it's useful service life. recommend schedule an oil change. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


▲ Fluid Condition

The BN level is low.

N SHP 15W40 (4)	2 Q I S)	Oct	2023	Nov2023 Jan20	24	
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0102342	GFL0102300	GFL0071626
Sample Date		Client Info		26 Jan 2024	17 Nov 2023	10 Oct 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		600	300	600
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				ABNORMAL	NORMAL	ABNORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>120	22	14	29
Chromium	ppm	ASTM D5185m	>20	<1	<1	<1
Nickel	ppm	ASTM D5185m	>5	<1	<1	1
Titanium	ppm	ASTM D5185m	>2	0	<1	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>20	3	1	0
_ead	ppm	ASTM D5185m	>40	2	0	<1
Copper	ppm	ASTM D5185m	>330	3	2	13
Γin	ppm	ASTM D5185m	>15	1	0	1
√anadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	5	25	5
Barium	ppm	ASTM D5185m	0	<1	0	5
Molybdenum	ppm	ASTM D5185m	60	58	52	55
Manganese	ppm	ASTM D5185m	0	2	1	9
Magnesium	ppm	ASTM D5185m	1010	629	563	710
Calcium	ppm	ASTM D5185m	1070	1665	1556	1276
Phosphorus	ppm	ASTM D5185m	1150	764	725	636
Zinc	ppm	ASTM D5185m	1270	1006	926	904
Sulfur	ppm	ASTM D5185m	2060	2388	2542	2379
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	8	8	△ 30
Sodium	ppm	ASTM D5185m		9	4	2
Potassium	ppm	ASTM D5185m	>20	4	3	9
Potassium INFRA-RED		ASTM D5185m method	>20 limit/base	4 current	3 history1	9 history2
INFRA-RED						
INFRA-RED Soot %	ppm	method	limit/base >4	current	history1	history2
INFRA-RED Soot % Nitration	ppm %	method *ASTM D7844	limit/base >4	current 0	history1	history2
INFRA-RED Soot % Nitration	% Abs/cm Abs/.1mm	method *ASTM D7844 *ASTM D7624 *ASTM D7415	limit/base >4 >20	current 0 12.2 24.7	history1 0 8.5	history2 0 12.6
INFRA-RED Soot % Nitration Sulfation	% Abs/cm Abs/.1mm	method *ASTM D7844 *ASTM D7624 *ASTM D7415	limit/base	current 0 12.2 24.7	history1 0 8.5 19.6	history2 0 12.6 22.8



OIL ANALYSIS REPORT





18 - Abnormal	
17	
Base	
© 16- Base 00 15-	
3 14	
13 Abnormal	
12 +	
11	
Oct10/23 -	


VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROP	EHIIES	method	iiiiii/base	current	riistory i	nistoryz
Visc @ 100°C	cSt	ASTM D445	15.4	14.5	14.8	14.8

GRAPHS













Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10849337 Test Package : FLEET

: GFL0102342 : 06072660

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved : 29 Jan 2024 Diagnosed : 31 Jan 2024

Diagnostician : Sean Felton

GFL Environmental - 035 - Greensboro

1236 Elon Place High Point, NC US 27263

Contact: JORGE COSTA jorge.costa@gflenv.com T: (336)668-3712

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)