


OIL ANALYSIS REPORT



Area
CHICAGO 95TH
Machine Id
CATERPILLAR 966M L-150-1 (S/N OKJP00662)
Component
Diesel Engine
Fluid
{not provided} (--- GAL)

Sample Rating Trend



FUEL



DIAGNOSIS

Recommendation

We advise that you check the fuel injection system. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a high amount of fuel present in the oil.

Fluid Condition

Fuel is present in the oil and is lowering the viscosity. The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	PCA0113127	PCA0105646	---
Sample Date	Client Info	21 Dec 2023	18 Oct 2023	---
Machine Age	hrs	12270	11983	---
Oil Age	hrs	1000	250	---
Oil Changed	Client Info	Changed	Changed	---
Sample Status		SEVERE	SEVERE	---

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	NEG	NEG	---
Glycol	WC Method	NEG	NEG	---

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	1	2	---
Chromium	ppm ASTM D5185m >20	<1	<1	---
Nickel	ppm ASTM D5185m >2	0	0	---
Titanium	ppm ASTM D5185m >2	<1	<1	---
Silver	ppm ASTM D5185m >2	0	0	---
Aluminum	ppm ASTM D5185m >25	1	1	---
Lead	ppm ASTM D5185m >40	1	1	---
Copper	ppm ASTM D5185m >330	<1	<1	---
Tin	ppm ASTM D5185m >15	<1	<1	---
Vanadium	ppm ASTM D5185m	<1	<1	---
Cadmium	ppm ASTM D5185m	0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	0	1	---
Barium	ppm ASTM D5185m	0	0	---
Molybdenum	ppm ASTM D5185m	42	37	---
Manganese	ppm ASTM D5185m	<1	<1	---
Magnesium	ppm ASTM D5185m	721	622	---
Calcium	ppm ASTM D5185m	756	713	---
Phosphorus	ppm ASTM D5185m	800	712	---
Zinc	ppm ASTM D5185m	951	845	---
Sulfur	ppm ASTM D5185m	2349	2128	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	2	2	---
Sodium	ppm ASTM D5185m	1	1	---
Potassium	ppm ASTM D5185m >20	<1	<1	---
Fuel	% ASTM D3524 >5	20.4	24.6	---




INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.2	0.2	---
Nitration	Abs/cm *ASTM D7624 >20	7.7	7.7	---
Sulfation	Abs/.1mm *ASTM D7415 >30	17.7	17.5	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.1	14.0	---
Base Number (BN)	mg KOH/g ASTM D2896	8.3	8.3	---









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	▲ 8.9	▲ 8.1	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0113127 **Received** : 01 Feb 2024
Lab Number : 06076482 **Tested** : 05 Feb 2024
Unique Number : 10858573 **Diagnosed** : 05 Feb 2024 - Jonathan Hester
Test Package : MOB 1 (Additional Tests: PercentFuel, TBN)

NORTH AMERICAN STEVEDORING CO
 9301 S KREITER AVE
 CHICAGO, IL
 US 60617
 Contact: PACO MARTINEZ
 paco.martinez@qsl.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: