




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**828027-3502**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0103852</b>	GFL0097356	GFL0089531
Sample Date	Client Info	<b>29 Jan 2024</b>	28 Nov 2023	28 Sep 2023
Machine Age	hrs	<b>11889</b>	10796	10796
Oil Age	hrs	<b>353</b>	9235	9235
Oil Changed	Client Info	<b>Changed</b>	N/A	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>5</b>	13	9
Chromium	ppm ASTM D5185m >5	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >2	<b>0</b>	<1	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>2</b>	3	0
Lead	ppm ASTM D5185m >30	<b>0</b>	0	<1
Copper	ppm ASTM D5185m >150	<b>1</b>	1	1
Tin	ppm ASTM D5185m >5	<b>0</b>	0	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>4</b>	5	4
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>62</b>	59	61
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>897</b>	923	980
Calcium	ppm ASTM D5185m 1070	<b>1093</b>	1017	1059
Phosphorus	ppm ASTM D5185m 1150	<b>962</b>	1058	1028
Zinc	ppm ASTM D5185m 1270	<b>1228</b>	1278	1270
Sulfur	ppm ASTM D5185m 2060	<b>2951</b>	3009	3142

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>2</b>	6	6
Sodium	ppm ASTM D5185m	<b>3</b>	6	5
Potassium	ppm ASTM D5185m >20	<b>3</b>	4	<1

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.4</b>	0.5	0.3
Nitration	Abs/cm *ASTM D7624 >20	<b>8.5</b>	9.8	7.7
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.0</b>	20.3	19.0

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.5</b>	17.3	15.0
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.9</b>	6.8	8.5







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.0</b>	14.12	14.2

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0103852 **Received** : 01 Feb 2024  
**Lab Number** : **06077592** **Diagnosed** : 02 Feb 2024  
**Unique Number** : 10859683 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 654S - Midlothian**  
 12230 Deergrove Road  
 Midlothian, VA  
 US 23112  
 Contact: Corbin Umphlet  
 cumphlet@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)