




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(YA130686)
Machine Id
AUTOCAR 10637
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	GFL0111396	GFL0058995	GFL0046007	
Sample Date	Client Info	03 Feb 2024	15 Oct 2022	14 Mar 2022	
Machine Age	hrs	Client Info	0	12671	11461
Oil Age	hrs	Client Info	0	0	0
Oil Changed	Client Info	N/A	Changed	Changed	
Sample Status		NORMAL	ABNORMAL	NORMAL	

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	18	35	5
Chromium	ppm ASTM D5185m >5	1	2	<1
Nickel	ppm ASTM D5185m >4	<1	<1	0
Titanium	ppm ASTM D5185m >2	<1	0	<1
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >15	<1	4	<1
Lead	ppm ASTM D5185m >25	1	<1	0
Copper	ppm ASTM D5185m >100	<1	1	<1
Tin	ppm ASTM D5185m >4	<1	<1	0
Antimony	ppm ASTM D5185m	---	---	---
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	3	7	7
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 60	63	65	60
Manganese	ppm ASTM D5185m 0	<1	<1	<1
Magnesium	ppm ASTM D5185m 1010	952	963	992
Calcium	ppm ASTM D5185m 1070	1031	1173	1165
Phosphorus	ppm ASTM D5185m 1150	972	999	1097
Zinc	ppm ASTM D5185m 1270	1225	1289	1307
Sulfur	ppm ASTM D5185m 2060	3009	3298	2698

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	6	8	4
Sodium	ppm ASTM D5185m	21	▲ 151	<1
Potassium	ppm ASTM D5185m >20	3	0	1

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.4	1.5	0.2
Nitration	Abs/cm *ASTM D7624 >20	6.7	11.7	6.7
Sulfation	Abs/.1mm *ASTM D7415 >30	18.6	24.9	19.5

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	13.8	18.3	15.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	8.0	9.7	9.6







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	14.4	13.3

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0111396 **Received** : 02 Feb 2024
Lab Number : 06078154 **Tested** : 05 Feb 2024
Unique Number : 10860245 **Diagnosed** : 05 Feb 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 004 - Newport - Central Coast
 427 Roberts Road
 Newport, NC
 US 28570
 Contact: Marquis Williams
 marquis.williams@gflenv.com
 T:
 F: (252)223-6010

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)