


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**121628-5087**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0117084</b>	PCA0104257	PCA0106254
Sample Date	Client Info		<b>27 Jan 2024</b>	14 Nov 2023	21 Sep 2023
Machine Age	mls	Client Info	<b>0</b>	58396	8805
Oil Age	mls	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>N/A</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>60</b>	40	38
Chromium	ppm	ASTM D5185m >20	<b>2</b>	<1	1
Nickel	ppm	ASTM D5185m >4	<b>&lt;1</b>	0	<1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>4</b>	4	5
Lead	ppm	ASTM D5185m >40	<b>3</b>	0	2
Copper	ppm	ASTM D5185m >330	<b>5</b>	8	17
Tin	ppm	ASTM D5185m >15	<b>2</b>	1	2
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>2</b>	5	6
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 50	<b>79</b>	69	74
Manganese	ppm	ASTM D5185m 0	<b>1</b>	<1	1
Magnesium	ppm	ASTM D5185m 950	<b>1161</b>	1055	1090
Calcium	ppm	ASTM D5185m 1050	<b>1215</b>	1262	1447
Phosphorus	ppm	ASTM D5185m 995	<b>1045</b>	1158	1271
Zinc	ppm	ASTM D5185m 1180	<b>1505</b>	1468	1636
Sulfur	ppm	ASTM D5185m 2600	<b>3166</b>	3163	3612

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>8</b>	6	8
Sodium	ppm	ASTM D5185m	<b>0</b>	3	0
Potassium	ppm	ASTM D5185m >20	<b>6</b>	6	5



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>1.7</b>	1.2	1
Nitration	Abs/cm	*ASTM D7624 >20	<b>14.7</b>	12.2	10.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>25.5</b>	23.0	21.1

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>22.3</b>	20.9	17.9
Base Number (BN)	mg KOH/g	ASTM D2896	<b>7.8</b>	8.2	8.5









# OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	12.0	11.9

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0117084 **Received** : 02 Feb 2024  
**Lab Number** : 06078911 **Diagnosed** : 05 Feb 2024  
**Unique Number** : 10861002 **Diagnostician** : Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #119**  
 39 INDUSTRIAL AVE  
 HASBROUCK HEIGHTS, NJ  
 US 07604  
 Contact: MIKE LONGETTE  
 mlongette@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (201)528-7053