


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
(51463Z) Walgreens - Tractor
Machine Id
[Walgreens - Tractor] 136A63331
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (11 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0106532	PCA0106538	---
Sample Date	Client Info		26 Jan 2024	08 Oct 2023	---
Machine Age	mls	Client Info	158364	97009	---
Oil Age	mls	Client Info	61364	57009	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	36	47	---
Chromium	ppm	ASTM D5185m >5	5	7	---
Nickel	ppm	ASTM D5185m >2	1	<1	---
Titanium	ppm	ASTM D5185m	0	0	---
Silver	ppm	ASTM D5185m >3	<1	0	---
Aluminum	ppm	ASTM D5185m >30	24	23	---
Lead	ppm	ASTM D5185m >30	0	<1	---
Copper	ppm	ASTM D5185m >150	64	90	---
Tin	ppm	ASTM D5185m >5	1	2	---
Vanadium	ppm	ASTM D5185m	0	0	---
Cadmium	ppm	ASTM D5185m	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	7	11	---
Barium	ppm	ASTM D5185m 0	0	0	---
Molybdenum	ppm	ASTM D5185m 50	56	56	---
Manganese	ppm	ASTM D5185m 0	2	2	---
Magnesium	ppm	ASTM D5185m 950	931	892	---
Calcium	ppm	ASTM D5185m 1050	1112	1352	---
Phosphorus	ppm	ASTM D5185m 995	965	978	---
Zinc	ppm	ASTM D5185m 1180	1209	1184	---
Sulfur	ppm	ASTM D5185m 2600	2097	2119	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	8	6	---
Sodium	ppm	ASTM D5185m	4	1	---
Potassium	ppm	ASTM D5185m >20	64	55	---
Glycol	%	*ASTM D2982	NEG	NEG	---




INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.7	0.8	---
Nitration	Abs/cm	*ASTM D7624 >20	10.3	10.7	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	23.3	26.0	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	22.2	28.3	---
Base Number (BN)	mg KOH/g	ASTM D2896	5.4	5.6	---





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.8	12.6

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0106532 **Received** : 05 Feb 2024
Lab Number : **06080510** **Tested** : 08 Feb 2024
Unique Number : 10862601 **Diagnosed** : 08 Feb 2024 - Jonathan Hester
Test Package : FLEET (Additional Tests: GLYCOL)

Transervice - Shop 1369 - Berkeley-Waxahachie
 710 Ovilla Road
 Waxahachie, TX
 US 75167
 Contact: Robert Beal
 rbeal@transervice.com
 T: (972)923-9928
 F: (972)923-9919

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)