


# **OIL ANALYSIS REPORT**

# Walgreens - Tractor [Walgreens - Tractor] 136A624118

Diesel Engine

PETRO CANADA DURON SHP 10W30 (11 GAL)



## DIAGNOSIS

#### Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

## Wear

Metal levels are typical for a new component breaking in.

#### Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.


### **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)				Jan 2024		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0103637		
Sample Date		Client Info		25 Jan 2024		
Machine Age	mls	Client Info		38445		
Oil Age	mls	Client Info		38445		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>2.0	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	56		
Chromium	ppm	ASTM D5185m	>20	1		
Nickel	ppm	ASTM D5185m	>4	5		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	<1		
Aluminum	ppm	ASTM D5185m	>20	18		
Lead	ppm	ASTM D5185m	>40	6		
Copper	ppm		>330	25		
Tin	ppm	ASTM D5185m	>15	5		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	50		
Barium	ppm	ASTM D5185m	0	3		
Molybdenum	ppm	ASTM D5185m	50	59		
Manganese	ppm	ASTM D5185m	0	6		
Magnesium	ppm	ASTM D5185m	950	445		
Calcium	ppm	ASTM D5185m	1050	1627		
Phosphorus	ppm	ASTM D5185m	995	957		
Zinc	ppm	ASTM D5185m	1180	1261		
Sulfur	ppm	ASTM D5185m	2600	2680		
CONTAMINAN		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	37		
Sodium	ppm	ASTM D5185m	00	6		
Potassium	ppm	ASTM D5185m		56		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.3		
Nitration	Abs/cm	*ASTM D7624	>20	9.0		
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.8		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.9		
Base Number (BN)	mg KOH/g	ASTM D2896		5.9		



# **OIL ANALYSIS REPORT**





Certificate L2367

Laboratory Sample No.

: PCA0103637 Lab Number : 06080517 **Unique Number** : 10862608

Test Package : FLEET

Received **Tested** 

: 06 Feb 2024 : 07 Feb 2024 - Don Baldridge Diagnosed

: 05 Feb 2024

6813 Chrisphalt Drive Bath Borough, PA US 18014

T: (610)837-8103

F: (610)837-8105

Contact: Stephen Mackes smackes@transervice.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)