




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
(C0807580) {UNASSIGNED}
 Machine Id
834020
 Component
Natural Gas Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (8 GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0109949	GFL0107222	GFL0101271
Sample Date	Client Info		02 Feb 2024	08 Jan 2024	04 Dec 2023
Machine Age	hrs	Client Info	1626	1350	1110
Oil Age	hrs	Client Info	428	152	511
Oil Changed	Client Info		Not Chngd	Not Chngd	Not Chngd
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	23	17	20
Chromium	ppm	ASTM D5185m >4	<1	<1	<1
Nickel	ppm	ASTM D5185m >2	0	1	0
Titanium	ppm	ASTM D5185m	0	0	0
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >9	2	4	2
Lead	ppm	ASTM D5185m >30	1	2	0
Copper	ppm	ASTM D5185m >35	6	4	5
Tin	ppm	ASTM D5185m >4	<1	2	<1
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	4	0	<1
Barium	ppm	ASTM D5185m 0	6	0	2
Molybdenum	ppm	ASTM D5185m 60	71	65	64
Manganese	ppm	ASTM D5185m 0	1	2	1
Magnesium	ppm	ASTM D5185m 1010	973	950	855
Calcium	ppm	ASTM D5185m 1070	1101	1111	1116
Phosphorus	ppm	ASTM D5185m 1150	818	921	828
Zinc	ppm	ASTM D5185m 1270	1225	1274	1113
Sulfur	ppm	ASTM D5185m 2060	2525	2686	2826

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	7	7	8
Sodium	ppm	ASTM D5185m	1	3	5
Potassium	ppm	ASTM D5185m >20	4	0	2

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0	0
Nitration	Abs/cm	*ASTM D7624 >20	9.4	9.4	9.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	23.0	20.3	19.3

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.6	15.4	15.0
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	3.7	2.4	4.1







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	13.22	13.5	13.3

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0109949 **Received** : 06 Feb 2024
Lab Number : **06081713** **Tested** : 09 Feb 2024
Unique Number : 10863804 **Diagnosed** : 09 Feb 2024 - Jonathan Hester
Test Package : FLEET (Additional Tests: KV40)

GFL Environmental - 010 - Stockbridge
 1280 Rum Creek Parkway
 Stockbridge, GA
 US 30281
 Contact: JOSHUA TINKER
 joshuatinker@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: