


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
FLEET
Machine Id
VOLVO VNR 26617

Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0113710	PCA0102840	PCA0095995
Sample Date	Client Info		01 Feb 2024	05 Sep 2023	08 Jun 2023
Machine Age	mls	Client Info	541603	522730	503566
Oil Age	mls	Client Info	18873	44020	24856
Oil Changed	Client Info		Not Changed	Changed	Not Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>4.0	<1.0	<1.0	<1.0
Water	WC Method	>0.1	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >80	14	35	21
Chromium	ppm	ASTM D5185m >6	<1	<1	<1
Nickel	ppm	ASTM D5185m >2	2	<1	1
Titanium	ppm	ASTM D5185m >2	0	0	0
Silver	ppm	ASTM D5185m >2	<1	<1	0
Aluminum	ppm	ASTM D5185m >20	3	<1	4
Lead	ppm	ASTM D5185m >95	2	<1	<1
Copper	ppm	ASTM D5185m >85	4	4	4
Tin	ppm	ASTM D5185m >9	<1	<1	<1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	0	<1	2
Barium	ppm	ASTM D5185m 0	0	0	0
Molybdenum	ppm	ASTM D5185m 50	59	55	59
Manganese	ppm	ASTM D5185m 0	<1	<1	<1
Magnesium	ppm	ASTM D5185m 950	919	959	980
Calcium	ppm	ASTM D5185m 1050	995	1071	1126
Phosphorus	ppm	ASTM D5185m 995	1050	996	1018
Zinc	ppm	ASTM D5185m 1180	1234	1261	1314
Sulfur	ppm	ASTM D5185m 2600	2894	2998	3684

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	5	4	5
Sodium	ppm	ASTM D5185m	6	14	2
Potassium	ppm	ASTM D5185m >20	5	3	3



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0.3	0.6	0.4
Nitration	Abs/cm	*ASTM D7624 >20	9.2	11.6	10.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.9	24.2	22.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.9	21.6	19.3
Base Number (BN)	mg KOH/g	ASTM D2896	6.7	4.6	5.6





OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.1	10.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0113710
Lab Number : 06081924
Unique Number : 10869369
Test Package : FLEET

Received : 06 Feb 2024
Tested : 07 Feb 2024
Diagnosed : 07 Feb 2024 - Wes Davis

PERDUE FARMS - ACCOMAC
 22520 LANKFORD HWY
 ACCOMAC, VA
 US 23301
 Contact: PEGGY KIMES
 peggy.kimes@perdue.com
 T: (757)787-5304
 F: (757)787-5208

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)