




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**228025-2001**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Confirm oil type. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0054117</b>	GFL0029270	---
Sample Date	Client Info	<b>01 Feb 2024</b>	21 Sep 2021	---
Machine Age	hrs	Client Info	<b>12063</b>	8193
Oil Age	hrs	Client Info	<b>1562</b>	753
Oil Changed	Client Info	<b>Changed</b>	Changed	---
Sample Status		<b>NORMAL</b>	NORMAL	---

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	---
Water	WC Method >0.2	<b>NEG</b>	NEG	---
Glycol	WC Method	<b>NEG</b>	NEG	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	<b>20</b>	45	---
Chromium	ppm ASTM D5185m >4	<b>&lt;1</b>	2	---
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	---
Titanium	ppm ASTM D5185m	<b>2</b>	3	---
Silver	ppm ASTM D5185m >2	<b>0</b>	<1	---
Aluminum	ppm ASTM D5185m >25	<b>7</b>	5	---
Lead	ppm ASTM D5185m >45	<b>3</b>	4	---
Copper	ppm ASTM D5185m >85	<b>&lt;1</b>	<1	---
Tin	ppm ASTM D5185m >4	<b>2</b>	<1	---
Antimony	ppm ASTM D5185m	<b>---</b>	0	---
Vanadium	ppm ASTM D5185m	<b>0</b>	<1	---
Cadmium	ppm ASTM D5185m	<b>0</b>	0	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>142</b>	9	---
Barium	ppm ASTM D5185m 0	<b>0</b>	0	---
Molybdenum	ppm ASTM D5185m 60	<b>11</b>	66	---
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	---
Magnesium	ppm ASTM D5185m 1010	<b>104</b>	1008	---
Calcium	ppm ASTM D5185m 1070	<b>1959</b>	1216	---
Phosphorus	ppm ASTM D5185m 1150	<b>984</b>	1093	---
Zinc	ppm ASTM D5185m 1270	<b>1187</b>	1331	---
Sulfur	ppm ASTM D5185m 2060	<b>3298</b>	2770	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	<b>24</b>	5	---
Sodium	ppm ASTM D5185m	<b>2</b>	5	---
Potassium	ppm ASTM D5185m >20	<b>6</b>	9	---

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.2</b>	0.9	---
Nitration	Abs/cm *ASTM D7624 >20	<b>8.1</b>	12.6	---
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>21.4</b>	24	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>17.5</b>	19.4	---
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.6</b>	6.6	---







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.5</b>	13.7	---

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0054117      **Received** : 07 Feb 2024  
**Lab Number** : 06082969      **Tested** : 08 Feb 2024  
**Unique Number** : 10870414      **Diagnosed** : 09 Feb 2024 - Don Baldrige  
**Test Package** : FLEET

**GFL Environmental - 630 - Northern A1 PA**  
 117 Moonlite Dr  
 Smithfield, PA  
 US 15478  
 Contact: MIKE NEWMAN  
 miken@northern1.com  
 T: (231)564-2362  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)