




OIL ANALYSIS REPORT

Sample Rating Trend

SOOT



Machine Id
723031-303001
 Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)



DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is an abnormal amount of solids and carbon present in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

| | method | limit/base | current | history1 | history2 |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | GFL0108109 | GFL0102441 | GFL0102412 |
| Sample Date | Client Info | | 31 Jan 2024 | 06 Jan 2024 | 12 Dec 2023 |
| Machine Age | hrs | Client Info | 20305 | 20159 | 20000 |
| Oil Age | hrs | Client Info | 0 | 0 | 0 |
| Oil Changed | Client Info | | Not Chngd | Not Chngd | N/A |
| Sample Status | | | ABNORMAL | NORMAL | NORMAL |

CONTAMINATION

| | method | limit/base | current | history1 | history2 |
|--------|-----------|------------|------------|----------|----------|
| Water | WC Method | >0.2 | NEG | NEG | NEG |
| Glycol | WC Method | | NEG | NEG | NEG |

WEAR METALS

| | method | limit/base | current | history1 | history2 |
|----------|--------|------------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m >80 | 53 | 27 | 8 |
| Chromium | ppm | ASTM D5185m >5 | 2 | <1 | <1 |
| Nickel | ppm | ASTM D5185m >2 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m >3 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m >30 | 6 | 3 | 2 |
| Lead | ppm | ASTM D5185m >30 | 0 | <1 | 0 |
| Copper | ppm | ASTM D5185m >150 | 1 | <1 | <1 |
| Tin | ppm | ASTM D5185m >5 | <1 | <1 | 0 |
| Vanadium | ppm | ASTM D5185m | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | 0 | 0 | 0 |

ADDITIVES

| | method | limit/base | current | history1 | history2 |
|------------|--------|------------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m 0 | 4 | <1 | 3 |
| Barium | ppm | ASTM D5185m 0 | 0 | 0 | <1 |
| Molybdenum | ppm | ASTM D5185m 60 | 54 | 54 | 59 |
| Manganese | ppm | ASTM D5185m 0 | <1 | <1 | <1 |
| Magnesium | ppm | ASTM D5185m 1010 | 834 | 906 | 965 |
| Calcium | ppm | ASTM D5185m 1070 | 893 | 1008 | 1073 |
| Phosphorus | ppm | ASTM D5185m 1150 | 924 | 956 | 1109 |
| Zinc | ppm | ASTM D5185m 1270 | 1138 | 1157 | 1311 |
| Sulfur | ppm | ASTM D5185m 2060 | 2360 | 2577 | 3153 |

CONTAMINANTS

| | method | limit/base | current | history1 | history2 |
|-----------|--------|-----------------|----------------|----------|----------|
| Silicon | ppm | ASTM D5185m >20 | 7 | 6 | 5 |
| Sodium | ppm | ASTM D5185m | 6 | 4 | 5 |
| Potassium | ppm | ASTM D5185m >20 | 0 | <1 | 1 |
| Fuel | % | ASTM D3524 >5 | <1.0 | <1.0 | <1.0 |

INFRA-RED





| | method | limit/base | current | history1 | history2 |
|-----------|----------|-----------------|-------------|----------|----------|
| Soot % | % | *ASTM D7844 >3 | ▲ 3 | 2.3 | 0.5 |
| Nitration | Abs/cm | *ASTM D7624 >20 | 16.1 | 12.4 | 6.6 |
| Sulfation | Abs/.1mm | *ASTM D7415 >30 | 29.1 | 23.9 | 19.3 |

FLUID DEGRADATION

| | method | limit/base | current | history1 | history2 |
|------------------|----------|-----------------|-------------|----------|----------|
| Oxidation | Abs/.1mm | *ASTM D7414 >25 | 27.8 | 20.7 | 14.4 |
| Base Number (BN) | mg KOH/g | ASTM D2896 9.8 | 5.6 | 7.7 | 8.3 |







OIL ANALYSIS REPORT



| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | NONE | NONE | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.2 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| Visc @ 100°C | cSt | ASTM D445 | 15.4 | 12.9 | 12.8 |

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0108109

Lab Number : 06082982

Unique Number : 10870427

Test Package : FLEET (Additional Tests: FuelDilution)

Received : 07 Feb 2024

Tested : 08 Feb 2024

Diagnosed : 08 Feb 2024 - Jonathan Hester

GFL Environmental - 837 - Harrison TS

22820 S State Route 291

Harrisonville, MO

US 64701

Contact: JOHNNY PEREZ

johnny.perez@gflenv.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)