


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**HINO 372134**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 10W30 (12 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0110648</b>	PCA0083837	PCA0083868
Sample Date	Client Info		<b>10 Jan 2024</b>	18 May 2023	25 Jan 2023
Machine Age	mls	Client Info	<b>205355</b>	190238	182939
Oil Age	mls	Client Info	<b>6830</b>	7299	5594
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>8</b>	9	12
Chromium	ppm	ASTM D5185m >20	<b>0</b>	2	<1
Nickel	ppm	ASTM D5185m >4	<b>0</b>	1	<1
Titanium	ppm	ASTM D5185m	<b>2</b>	20	73
Silver	ppm	ASTM D5185m >3	<b>0</b>	2	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	5	2
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	5	1
Copper	ppm	ASTM D5185m >330	<b>&lt;1</b>	2	<1
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	2	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	1	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	2	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	<b>2</b>	14	72
Barium	ppm	ASTM D5185m 0	<b>0</b>	19	0
Molybdenum	ppm	ASTM D5185m 50	<b>62</b>	36	18
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	<1
Magnesium	ppm	ASTM D5185m 950	<b>980</b>	606	551
Calcium	ppm	ASTM D5185m 1050	<b>1120</b>	947	1664
Phosphorus	ppm	ASTM D5185m 995	<b>1068</b>	756	1015
Zinc	ppm	ASTM D5185m 1180	<b>1269</b>	928	1260
Sulfur	ppm	ASTM D5185m 2600	<b>3218</b>	2844	4151

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	6	5
Sodium	ppm	ASTM D5185m	<b>5</b>	5	5
Potassium	ppm	ASTM D5185m >20	<b>0</b>	7	1



## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.8</b>	1	0.8
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.9</b>	10.6	10.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.2</b>	20.7	20.8

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.2</b>	17.3	16.8
Base Number (BN)	mg KOH/g	ASTM D2896	<b>6.1</b>	8.8	8.1









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	<b>11.5</b>	11.8	12.2

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0110648 **Received** : 09 Feb 2024  
**Lab Number** : **06084517** **Tested** : 09 Feb 2024  
**Unique Number** : 10871962 **Diagnosed** : 09 Feb 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #123**  
 66 KELLER AVENUE  
 LANCASTER, PA  
 US 17601  
 Contact: RON ROBERTS  
 roberts@millertransgroup.com  
 T: (717)945-6205  
 F: (717)945-5818

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)