




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
945001-152555
 Component
Natural Gas Engine
 Fluid
PETRO CANADA DURON GEO LD 15W40 (8 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0088459	GFL0073226	GFL0073230
Sample Date	Client Info		05 Feb 2024	16 Nov 2023	16 May 2023
Machine Age	hrs	Client Info	20955	20389	19391
Oil Age	hrs	Client Info	600	19391	650
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	ABNORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	20	19	20
Chromium	ppm	ASTM D5185m >5	3	2	3
Nickel	ppm	ASTM D5185m >4	3	<1	1
Titanium	ppm	ASTM D5185m >5	<1	<1	0
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >25	3	3	4
Lead	ppm	ASTM D5185m >40	8	7	8
Copper	ppm	ASTM D5185m >150	9	4	8
Tin	ppm	ASTM D5185m >4	2	4	<1
Vanadium	ppm	ASTM D5185m	<1	<1	0
Cadmium	ppm	ASTM D5185m	<1	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	4	19	4
Barium	ppm	ASTM D5185m 5	15	0	0
Molybdenum	ppm	ASTM D5185m 50	60	60	75
Manganese	ppm	ASTM D5185m 0	<1	<1	1
Magnesium	ppm	ASTM D5185m 560	515	720	546
Calcium	ppm	ASTM D5185m 1510	1455	1372	1620
Phosphorus	ppm	ASTM D5185m 780	661	685	713
Zinc	ppm	ASTM D5185m 870	882	959	971
Sulfur	ppm	ASTM D5185m 2040	2526	2439	2432

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	8	▲ 25	5
Sodium	ppm	ASTM D5185m	6	3	12
Potassium	ppm	ASTM D5185m >20	2	<1	3

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0	0
Nitration	Abs/cm	*ASTM D7624 >20	11.5	11.6	12.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	23.1	22.0	26.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	18.9	19.4	22.4
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	3.3	4.6	3.0







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.1	14.1	14.0	14.3

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0088459 **Received** : 12 Feb 2024
Lab Number : 06085662 **Tested** : 12 Feb 2024
Unique Number : 10873107 **Diagnosed** : 12 Feb 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 146 - Augusta
 1064 Franke Industrial
 Augusta, GA
 US 30909
 Contact: JEFFERY WASHINGTON
 jeff.washington@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)