




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
12036

Component
Diesel Engine

Fluid
CHEVRON DELO 400 SDE SAE 15W40 (32 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	GFL0068878	GFL0068859	GFL0097154	
Sample Date	Client Info	08 Feb 2024	13 Jan 2024	22 Dec 2023	
Machine Age	hrs	Client Info	13968	13843	13730
Oil Age	hrs	Client Info	125	538	425
Oil Changed	Client Info	Not Changed	Changed	Not Changed	
Sample Status		NORMAL	NORMAL	NORMAL	

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >3.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	0.0	0.0

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	5	11	10
Chromium	ppm ASTM D5185m >5	<1	<1	<1
Nickel	ppm ASTM D5185m >4	0	0	0
Titanium	ppm ASTM D5185m >2	<1	0	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >15	3	3	3
Lead	ppm ASTM D5185m >25	0	0	0
Copper	ppm ASTM D5185m >100	0	1	<1
Tin	ppm ASTM D5185m >4	0	0	0
Vanadium	ppm ASTM D5185m	0	<1	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	6	1	1
Barium	ppm ASTM D5185m	0	0	0
Molybdenum	ppm ASTM D5185m	55	55	62
Manganese	ppm ASTM D5185m	<1	0	0
Magnesium	ppm ASTM D5185m	860	859	866
Calcium	ppm ASTM D5185m	932	913	1007
Phosphorus	ppm ASTM D5185m 760	978	953	937
Zinc	ppm ASTM D5185m 800	1129	1151	1122
Sulfur	ppm ASTM D5185m 3000	2808	2868	2835

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	7	5	5
Sodium	ppm ASTM D5185m	64	124	97
Potassium	ppm ASTM D5185m >20	0	4	1

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >6	0.2	0.4	0.4
Nitration	Abs/cm *ASTM D7624 >20	5.8	8.3	7.3
Sulfation	Abs/.1mm *ASTM D7415 >30	17.6	18.3	18.1

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	13.1	14.4	13.8
Base Number (BN)	mg KOH/g ASTM D2896 10	8.3	7.9	8.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.6	13.1	12.9	13.3

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0068878
Lab Number : **06085873**
Unique Number : 10873318
Test Package : FLEET
Received : 12 Feb 2024
Tested : 13 Feb 2024
Diagnosed : 13 Feb 2024 - Jonathan Hester

GFL Environmental - 073 - Warner Robins - Transwaste
 155 Story Road
 Warner Robins, GA
 US 31093
 Contact: JOSH MALONEY
 jmaloney@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)