



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL




Area
(YA113932)

Machine Id
2433

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (8 GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0099830	GFL0089981	GFL0074440
Sample Date	Client Info	10 Feb 2024	23 Jan 2024	29 Sep 2023
Machine Age	hrs	18690	512899	512899
Oil Age	hrs	600	512899	512899
Oil Changed	Client Info	Changed	Changed	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >75	26	22	53
Chromium	ppm ASTM D5185m >4	<1	<1	<1
Nickel	ppm ASTM D5185m >5	0	0	<1
Titanium	ppm ASTM D5185m >2	0	0	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >54	1	<1	1
Lead	ppm ASTM D5185m >20	<1	1	2
Copper	ppm ASTM D5185m >240	2	3	6
Tin	ppm ASTM D5185m >5	0	0	<1
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	4	3	1
Barium	ppm ASTM D5185m 0	8	0	0
Molybdenum	ppm ASTM D5185m 60	66	59	63
Manganese	ppm ASTM D5185m 0	0	<1	<1
Magnesium	ppm ASTM D5185m 1010	939	987	937
Calcium	ppm ASTM D5185m 1070	1048	1104	1037
Phosphorus	ppm ASTM D5185m 1150	873	1086	1039
Zinc	ppm ASTM D5185m 1270	1219	1290	1271
Sulfur	ppm ASTM D5185m 2060	2823	3261	3189

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >35	10	4	5
Sodium	ppm ASTM D5185m	<1	2	3
Potassium	ppm ASTM D5185m >20	2	2	18

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	1	0.6	1.2
Nitration	Abs/cm *ASTM D7624 >20	11.2	6.4	7.2
Sulfation	Abs/.1mm *ASTM D7415 >30	22.1	18.7	20.0

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	19.2	13.9	14.2
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.7	8.5	8.8







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.7	14.0

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0099830
 Lab Number : 06088560
 Unique Number : 10876005
 Test Package : FLEET

Received : 14 Feb 2024
 Tested : 15 Feb 2024
 Diagnosed : 15 Feb 2024 - Wes Davis

GFL Environmental - 018 - Fayetteville
 4621 Marracco Drive
 Hope Mills, NC
 US 28348

Contact: Robert Carter
 robert.carter@gflenv.com

T: (910)596-1170

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)