




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**721018-361460**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0104938</b>	GFL0104907	GFL0104916
Sample Date	Client Info		<b>05 Feb 2024</b>	25 Jan 2024	03 Jan 2024
Machine Age	hrs	Client Info	<b>1308</b>	1211	10042
Oil Age	hrs	Client Info	<b>0</b>	0	467
Oil Changed	Client Info		<b>N/A</b>	N/A	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>16</b>	9	35
Chromium	ppm	ASTM D5185m >20	<b>2</b>	1	4
Nickel	ppm	ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	2	2
Lead	ppm	ASTM D5185m >40	<b>2</b>	2	5
Copper	ppm	ASTM D5185m >330	<b>2</b>	1	2
Tin	ppm	ASTM D5185m >15	<b>2</b>	1	4
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>1</b>	<1	13
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	5
Molybdenum	ppm	ASTM D5185m 60	<b>57</b>	56	55
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	1	2
Magnesium	ppm	ASTM D5185m 1010	<b>971</b>	854	814
Calcium	ppm	ASTM D5185m 1070	<b>1002</b>	957	1117
Phosphorus	ppm	ASTM D5185m 1150	<b>1012</b>	963	883
Zinc	ppm	ASTM D5185m 1270	<b>1239</b>	1150	983
Sulfur	ppm	ASTM D5185m 2060	<b>3066</b>	2828	2492

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>6</b>	4	14
Sodium	ppm	ASTM D5185m	<b>19</b>	15	28
Potassium	ppm	ASTM D5185m >20	<b>1</b>	3	2

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.5</b>	0.4	0.9
Nitration	Abs/cm	*ASTM D7624 >20	<b>8.2</b>	6.7	10.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.2</b>	19.0	21.4

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.5</b>	14.2	18.8
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.0</b>	7.7	7.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.3</b>	13.5	13.9

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0104938 **Received** : 15 Feb 2024  
**Lab Number** : **06089817** **Tested** : 16 Feb 2024  
**Unique Number** : 10882670 **Diagnosed** : 16 Feb 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 820 - Joplin Hauling**  
 3700 West 7th Street  
 Joplin, MO  
 US 64801  
 Contact: James Jarrett  
 jjarrett@gflenv.com  
 T: (417)310-2802  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)