




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**4631M**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (6 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0106667</b>	GFL0097726	GFL0087337
Sample Date	Client Info		<b>05 Feb 2024</b>	24 Nov 2023	12 Jul 2023
Machine Age	hrs	Client Info	<b>20553</b>	19914	18748
Oil Age	hrs	Client Info	<b>639</b>	583	641
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	0.0

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	<b>23</b>	48	▲ 141
Chromium	ppm	ASTM D5185m >20	<b>1</b>	1	4
Nickel	ppm	ASTM D5185m >4	<b>0</b>	0	1
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>10</b>	7	9
Lead	ppm	ASTM D5185m >40	<b>0</b>	0	0
Copper	ppm	ASTM D5185m >330	<b>&lt;1</b>	2	16
Tin	ppm	ASTM D5185m >15	<b>0</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>5</b>	0	5
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>60</b>	63	65
Manganese	ppm	ASTM D5185m 0	<b>0</b>	0	2
Magnesium	ppm	ASTM D5185m 1010	<b>988</b>	1099	926
Calcium	ppm	ASTM D5185m 1070	<b>1113</b>	1245	1113
Phosphorus	ppm	ASTM D5185m 1150	<b>1136</b>	1224	973
Zinc	ppm	ASTM D5185m 1270	<b>1337</b>	1581	1301
Sulfur	ppm	ASTM D5185m 2060	<b>3371</b>	3762	3453

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>5</b>	5	11
Sodium	ppm	ASTM D5185m	<b>6</b>	17	▲ 85
Potassium	ppm	ASTM D5185m >20	<b>2</b>	2	6

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	<b>0.2</b>	0.5	1.4
Nitration	Abs/cm	*ASTM D7624 >20	<b>5.8</b>	7.1	10.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>17.8</b>	18.9	22.5

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>13.3</b>	14.2	17.4
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>8.9</b>	8.8	7.5







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.9</b>	14.2	14.1

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0106667  
**Lab Number** : 06092628  
**Unique Number** : 10885481  
**Test Package** : FLEET

**Received** : 19 Feb 2024  
**Tested** : 20 Feb 2024  
**Diagnosed** : 20 Feb 2024 - Wes Davis

**GFL Environmental - 405 - Arbor Hills**  
 7400 Napier Rd  
 NORTHVILLE, MI  
 US 48168  
 Contact: John Nahal  
 jnahal@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: