




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**420010-1309**

Component  
**Diesel Engine**

Fluid  
**CHEVRON DELO 400 XLE 15W40 (10 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0096243</b>	GFL0096251	GFL0064440
Sample Date	Client Info	<b>12 Feb 2024</b>	19 Oct 2023	11 Sep 2023
Machine Age	hrs	<b>10014</b>	216952	9134
Oil Age	hrs	<b>10014</b>	0	385
Oil Changed	Client Info	<b>Changed</b>	Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >2.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>16</b>	21	15
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	1	<1
Nickel	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	0
Titanium	ppm ASTM D5185m	<b>11</b>	11	10
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>3</b>	6	5
Lead	ppm ASTM D5185m >40	<b>2</b>	2	2
Copper	ppm ASTM D5185m >330	<b>0</b>	<1	<1
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	<1	<1

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	<b>70</b>	83	129
Barium	ppm ASTM D5185m	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m	<b>48</b>	57	58
Manganese	ppm ASTM D5185m	<b>&lt;1</b>	<1	1
Magnesium	ppm ASTM D5185m	<b>649</b>	722	737
Calcium	ppm ASTM D5185m	<b>1369</b>	1509	1671
Phosphorus	ppm ASTM D5185m 760	<b>657</b>	788	746
Zinc	ppm ASTM D5185m 830	<b>780</b>	886	880
Sulfur	ppm ASTM D5185m 2770	<b>2685</b>	3702	3507

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>4</b>	5	5
Sodium	ppm ASTM D5185m	<b>4</b>	6	5
Potassium	ppm ASTM D5185m >20	<b>5</b>	10	8

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.5</b>	0.5	0.4
Nitration	Abs/cm *ASTM D7624 >20	<b>11.0</b>	11.5	9.6
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>23.3</b>	23.9	20.9

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>18.6</b>	18.8	15.7
Base Number (BN)	mg KOH/g ASTM D2896 10.7	<b>5.9</b>	6.7	7.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.9	<b>13.4</b>	13.7	13.8

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0096243 **Received** : 21 Feb 2024  
**Lab Number** : 06096085 **Tested** : 22 Feb 2024  
**Unique Number** : 10888938 **Diagnosed** : 22 Feb 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 624 - Elmira Hauling**  
 10164 M-32  
 Elmira, MI  
 US 49730  
 Contact: ANDY GROBASKI  
 andyg@americanwaste.org  
 T: (989)370-2941  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)