


# **OIL ANALYSIS REPORT**

### Sample Rating Trend





Machine Id DT711

**Transmission (Auto)** 

**COGNIS EMGARD 2805 ATF (--- QTS)** 

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the fluid.


### **Fluid Condition**

The condition of the fluid is acceptable for the time in service.

		Sep 2020 /	Apr2021 Nov2021 May20	22 Nov2022 Apr2023 Sep2023	Feb2024	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0111616	PCA0101897	PCA0095213
Sample Date		Client Info		09 Feb 2024	28 Sep 2023	14 Apr 2023
Machine Age	mls	Client Info		0	0	0
Oil Age	mls	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METAL	.S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	66	69	107
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m	>50	22	24	43
Lead	ppm	ASTM D5185m	>50	37	45	48
Copper	ppm	ASTM D5185m	>225	20	17	17
Tin	ppm	ASTM D5185m	>10	3	2	3
Vanadium	ppm	ASTM D5185m	>10	0	0	0
Cadmium		ASTM D5185m		0	0	0
	ppm			<u> </u>		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		111	130	157
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		4	5	1
Manganese	ppm	ASTM D5185m		<1	<1	2
Magnesium	ppm	ASTM D5185m		14	22	4
Calcium	ppm	ASTM D5185m		103	181	104
Phosphorus	ppm	ASTM D5185m		304	393	388
Zinc	ppm	ASTM D5185m		41	82	16
Sulfur	ppm	ASTM D5185m		1492	1832	1373
CONTAMINAN	ITS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	5	6
Sodium	ppm	ASTM D5185m		10	9	10
Potassium	ppm	ASTM D5185m	>20	4	<1	4
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water		*Visual	ZU. I	NEG	NEG	NEG
Pree water	scalar	visual		NEG		" DAVID WEDD





# **OIL ANALYSIS REPORT**




FLUID PROF	PERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	35.3	36.9	36.5
SAMPLE IMA	AGES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

## **GRAPHS**









Certificate L2367

Laboratory Sample No.

: PCA0111616 Lab Number : 06096541 Unique Number: 10889394 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 21 Feb 2024

**Tested** : 22 Feb 2024 Diagnosed : 22 Feb 2024 - Wes Davis

NW WHITE & CO - BEAUFORT DIVISION 1491 YENMASSEE HIGHWAY

VARNVILLE, SC US 29944

Contact: VINCENT BULLOCK bullockvince514@gmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: