


OIL ANALYSIS REPORT

Sample Rating Trend



749012

Component

Transmission (Auto)

PETRO CANADA DuraDrive HD Synthetic 6

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

| 668 (27 QTS) | | | | | | |
|------------------|-----------|-------------|------------|-------------|---------------|-----------|
| | | | ::±/ | Feb 2024 | المراجعة الما | history.0 |
| SAMPLE INFOR | RIVIATION | | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | GFL0092064 | | |
| Sample Date | | Client Info | | 15 Feb 2024 | | |
| Machine Age | hrs | Client Info | | 15036 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINA | TION | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR META | LS | method | limit/base | current | history1 | history2 |
| ron | ppm | ASTM D5185m | >325 | 59 | | |
| Chromium | ppm | ASTM D5185m | >2 | 0 | | |
| Nickel | ppm | ASTM D5185m | >2 | 0 | | |
| Titanium | ppm | ASTM D5185m | >3 | 0 | | |
| Silver | ppm | ASTM D5185m | >5 | 0 | | |
| Aluminum | ppm | ASTM D5185m | >75 | 37 | | |
| _ead | ppm | ASTM D5185m | >40 | 1 | | |
| Copper | ppm | ASTM D5185m | >50 | 15 | | |
| Γin | ppm | ASTM D5185m | >10 | 2 | | |
| /anadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 61 | | |
| Barium | ppm | ASTM D5185m | | <1 | | |
| Molybdenum | ppm | ASTM D5185m | | <1 | | |
| Manganese | ppm | ASTM D5185m | | <1 | | |
| Magnesium | ppm | ASTM D5185m | | 6 | | |
| Calcium | ppm | ASTM D5185m | | 41 | | |
| Phosphorus | ppm | ASTM D5185m | | 195 | | |
| Zinc | ppm | ASTM D5185m | | 0 | | |
| Sulfur | ppm | ASTM D5185m | | 997 | | |
| CONTAMINA | NTS | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >20 | 7 | | |
| Sodium | ppm | ASTM D5185m | | 6 | | |
| Potassium | ppm | ASTM D5185m | >20 | 3 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | NONE | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| | | | | | | |





OIL ANALYSIS REPORT






GRAPHS









Certificate L2367

Laboratory Sample No.

: GFL0092064 Lab Number : 06096552 Unique Number : 10889405 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 21 Feb 2024 Tested

: 22 Feb 2024 Diagnosed

: 23 Feb 2024 - Sean Felton

GFL Environmental - 856 - Houston South 8515 Highway 6 South

Houston, TX US 77083

Contact: Apolinar Zacarias pzacariascano@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: