


# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**630778**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 10W30 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

### Wear

Metal levels are typical for a new component breaking in.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>PCA0118912</b>	PCA0101331	PCA0089667
Sample Date	Client Info			<b>17 Feb 2024</b>	27 Jun 2023	30 Jan 2023
Machine Age	mls	Client Info		<b>39999</b>	25175	9358
Oil Age	mls	Client Info		<b>0</b>	0	0
Oil Changed	Client Info			<b>Changed</b>	Changed	Not Changed
Sample Status				<b>NORMAL</b>	NORMAL	NORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>31</b>	64	34
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>0</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	<1	<1
Aluminum	ppm	ASTM D5185m	>20	<b>16</b>	29	15
Lead	ppm	ASTM D5185m	>40	<b>0</b>	<1	2
Copper	ppm	ASTM D5185m	>330	<b>10</b>	34	22
Tin	ppm	ASTM D5185m	>15	<b>1</b>	2	2
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m		<b>0</b>	0	0



ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	<b>32</b>	30	66
Barium	ppm	ASTM D5185m	0	<b>0</b>	0	1
Molybdenum	ppm	ASTM D5185m	50	<b>55</b>	3	3
Manganese	ppm	ASTM D5185m	0	<b>&lt;1</b>	2	2
Magnesium	ppm	ASTM D5185m	950	<b>881</b>	740	772
Calcium	ppm	ASTM D5185m	1050	<b>1147</b>	1400	1519
Phosphorus	ppm	ASTM D5185m	995	<b>997</b>	805	772
Zinc	ppm	ASTM D5185m	1180	<b>1177</b>	946	971
Sulfur	ppm	ASTM D5185m	2600	<b>2939</b>	3094	3928

CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>3</b>	21	21
Sodium	ppm	ASTM D5185m		<b>2</b>	4	4
Potassium	ppm	ASTM D5185m	>20	<b>37</b>	80	46

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.4</b>	0.5	0.2
Nitration	Abs/cm	*ASTM D7624	>20	<b>10.3</b>	12.0	9.9
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>21.6</b>	25.9	20.1

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>18.2</b>	21.0	15.4
Base Number (BN)	mg KOH/g	ASTM D2896		<b>6.7</b>	5.8	6.7









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	12.00	11.8	12.3

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0118912      **Received** : 22 Feb 2024  
**Lab Number** : 06096761      **Tested** : 23 Feb 2024  
**Unique Number** : 10889614      **Diagnosed** : 23 Feb 2024 - Wes Davis  
**Test Package** : MOB 1 ( Additional Tests: TBN )

**MILLER TRUCK LEASING #119**  
 39 INDUSTRIAL AVE  
 HASBROUCK HEIGHTS, NJ  
 US 07604  
 Contact: MIKE LONGETTE  
 mlongette@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (201)528-7053