



# OIL ANALYSIS REPORT

Sample Rating Trend


**NORMAL**



Machine Id  
**721032-362019**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**



## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0101985</b>	GFL0101982	GFL0101962
Sample Date	Client Info	<b>21 Feb 2024</b>	26 Jan 2024	18 Dec 2023
Machine Age	hrs	<b>4005</b>	3873	3716
Oil Age	hrs	<b>435</b>	303	146
Oil Changed	Client Info	<b>Not Changed</b>	Not Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>11</b>	7	4
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >4	<b>0</b>	<1	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Silver	ppm ASTM D5185m >3	<b>0</b>	<1	0
Aluminum	ppm ASTM D5185m >20	<b>4</b>	5	2
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	1	<1
Copper	ppm ASTM D5185m >330	<b>1</b>	<1	<1
Tin	ppm ASTM D5185m >15	<b>1</b>	<1	0
Vanadium	ppm ASTM D5185m	<b>0</b>	<1	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>2</b>	5	2
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>55</b>	57	57
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	0
Magnesium	ppm ASTM D5185m 1010	<b>843</b>	910	894
Calcium	ppm ASTM D5185m 1070	<b>1004</b>	1012	1016
Phosphorus	ppm ASTM D5185m 1150	<b>933</b>	1067	925
Zinc	ppm ASTM D5185m 1270	<b>1095</b>	1251	1152
Sulfur	ppm ASTM D5185m 2060	<b>2657</b>	3187	2962

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	4	3
Sodium	ppm ASTM D5185m	<b>4</b>	4	2
Potassium	ppm ASTM D5185m >20	<b>4</b>	7	2

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.4</b>	0.3	0.2
Nitration	Abs/cm *ASTM D7624 >20	<b>8.1</b>	7.2	5.9
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>19.1</b>	19.1	18.1

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.7</b>	15.1	13.9
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.4</b>	8.1	8.4







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>12.8</b>	13.2	13.6

## GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0101985  
 Lab Number : 06096831  
 Unique Number : 10889684  
 Test Package : FLEET

Received : 22 Feb 2024  
 Tested : 23 Feb 2024  
 Diagnosed : 23 Feb 2024 - Wes Davis

**GFL Environmental - 894 - Ada Hauling**  
 1904 North Broadway, Suite D  
 Ada, OK  
 US 74820  
 Contact: Johnny Spurlock  
 jspurlock@gflenv.com  
 T: (405)664-4476  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)