




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**912076**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0092811</b>	GFL0092784	GFL0080773
Sample Date	Client Info		<b>21 Feb 2024</b>	31 Oct 2023	28 Aug 2023
Machine Age	hrs	Client Info	<b>3376</b>	3376	3377
Oil Age	hrs	Client Info	<b>3376</b>	3376	0
Oil Changed	Client Info		<b>Not Chngd</b>	N/A	Not Chngd
Sample Status			<b>NORMAL</b>	NORMAL	ABNORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>21</b>	12	25
Chromium	ppm	ASTM D5185m >20	<b>1</b>	<1	1
Nickel	ppm	ASTM D5185m >5	<b>4</b>	<1	▲ 11
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>1</b>	2	<1
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	1
Copper	ppm	ASTM D5185m >330	<b>5</b>	<1	6
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>&lt;1</b>	2	2
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m 60	<b>59</b>	60	65
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	0	1
Magnesium	ppm	ASTM D5185m 1010	<b>911</b>	906	1079
Calcium	ppm	ASTM D5185m 1070	<b>1027</b>	1034	1197
Phosphorus	ppm	ASTM D5185m 1150	<b>917</b>	962	1059
Zinc	ppm	ASTM D5185m 1270	<b>1132</b>	1186	1393
Sulfur	ppm	ASTM D5185m 2060	<b>2221</b>	2934	3060

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>3</b>	3	5
Sodium	ppm	ASTM D5185m	<b>8</b>	1	6
Potassium	ppm	ASTM D5185m >20	<b>0</b>	1	3

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.8</b>	0.6	0.7
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.1</b>	7.2	10.0
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>22.5</b>	19.5	22.8

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.5</b>	14.6	19.6
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>5.1</b>	7.9	4.9







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE
Yellow Metal	scalar	*Visual	NONE	<b>NONE</b>	NONE
Precipitate	scalar	*Visual	NONE	<b>NONE</b>	NONE
Silt	scalar	*Visual	NONE	<b>NONE</b>	NONE
Debris	scalar	*Visual	NONE	<b>NONE</b>	NONE
Sand/Dirt	scalar	*Visual	NONE	<b>NONE</b>	NONE
Appearance	scalar	*Visual	NORML	<b>NORML</b>	NORML
Odor	scalar	*Visual	NORML	<b>NORML</b>	NORML
Emulsified Water	scalar	*Visual	>0.2	<b>NEG</b>	NEG
Free Water	scalar	*Visual		<b>NEG</b>	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.6

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0092811 **Received** : 26 Feb 2024  
**Lab Number** : **06099781** **Tested** : 27 Feb 2024  
**Unique Number** : 10898011 **Diagnosed** : 27 Feb 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 455 - Flint**  
 2051 W. Bristol Rd  
 Flint Township, MI  
 US 48507  
 Contact: MARK WOMBLE  
 mwomble@gflenv.com  
 T: (586)825-9514  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)