



OIL ANALYSIS REPORT

Sample Rating Trend


GLYCOL



Machine Id
925039-260315

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)



DIAGNOSIS

Recommendation

We advise that you check for possible coolant leak. Check for low coolant level. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

Sodium and/or potassium levels are high. Fuel content negligible.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0108071	GFL0109762	GFL0102409
Sample Date	Client Info	19 Feb 2024	29 Jan 2024	06 Dec 2023
Machine Age	hrs	23236	23060	22913
Oil Age	hrs	176	600	0
Oil Changed	Client Info	Not Chngd	Changed	N/A
Sample Status		ABNORMAL	ABNORMAL	ABNORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	0.1
Water	WC Method >0.2	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	7	21	18
Chromium	ppm ASTM D5185m >4	<1	<1	<1
Nickel	ppm ASTM D5185m >2	0	<1	<1
Titanium	ppm ASTM D5185m	0	0	<1
Silver	ppm ASTM D5185m >2	0	<1	0
Aluminum	ppm ASTM D5185m >25	2	4	3
Lead	ppm ASTM D5185m >45	2	4	1
Copper	ppm ASTM D5185m >85	0	2	2
Tin	ppm ASTM D5185m >4	0	<1	<1
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	<1

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	4	11	5
Barium	ppm ASTM D5185m 0	0	0	12
Molybdenum	ppm ASTM D5185m 60	66	73	64
Manganese	ppm ASTM D5185m 0	<1	<1	<1
Magnesium	ppm ASTM D5185m 1010	865	928	906
Calcium	ppm ASTM D5185m 1070	1000	1017	995
Phosphorus	ppm ASTM D5185m 1150	967	1097	1022
Zinc	ppm ASTM D5185m 1270	1176	1291	1173
Sulfur	ppm ASTM D5185m 2060	2906	3203	3399

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	10	14	12
Sodium	ppm ASTM D5185m	▲ 372	▲ 413	▲ 184
Potassium	ppm ASTM D5185m >20	0	8	6
Glycol	% *ASTM D2982	NEG	NEG	NEG

INFRA-RED




method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	0.4	0.8	0.6
Nitration	Abs/cm *ASTM D7624 >20	7.7	9.9	8.1
Sulfation	Abs/.1mm *ASTM D7415 >30	19.3	20.5	19.7

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	14.5	15.9	14.9
Base Number (BN)	mg KOH/g ASTM D2896 9.8	9.6	8.7	8.5







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.8	13.4

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513

Sample No. : GFL0108071

Lab Number : **06100831**

Unique Number : 10899061

Test Package : FLEET (Additional Tests: Glycol)

Received : 26 Feb 2024

Tested : 28 Feb 2024

Diagnosed : 28 Feb 2024 - Jonathan Hester

GFL Environmental - 836 - Kansas City Hauling

7801 East Truman Road

Kansas City, MO

US 64126

Contact: Loyce Stewart

loyce.stewart@gflenv.com

T:

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)