




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**728046-361685**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0105268</b>	GFL0105319	GFL0105216
Sample Date	Client Info	<b>26 Feb 2024</b>	14 Feb 2024	02 Feb 2024
Machine Age	hrs	<b>33460</b>	33318	16651
Oil Age	hrs	<b>300</b>	600	450
Oil Changed	Client Info	<b>Not Changed</b>	Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>10</b>	4	13
Chromium	ppm ASTM D5185m >20	<b>1</b>	0	<1
Nickel	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm ASTM D5185m >3	<b>&lt;1</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>2</b>	2	4
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	<1	<1
Copper	ppm ASTM D5185m >330	<b>&lt;1</b>	<1	2
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	<1	0
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>&lt;1</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>2</b>	3	36
Barium	ppm ASTM D5185m 0	<b>1</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>61</b>	55	64
Manganese	ppm ASTM D5185m 0	<b>&lt;1</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>935</b>	886	889
Calcium	ppm ASTM D5185m 1070	<b>1046</b>	959	1026
Phosphorus	ppm ASTM D5185m 1150	<b>938</b>	961	966
Zinc	ppm ASTM D5185m 1270	<b>1231</b>	1194	1194
Sulfur	ppm ASTM D5185m 2060	<b>3389</b>	2970	2969

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>5</b>	4	18
Sodium	ppm ASTM D5185m	<b>10</b>	6	33
Potassium	ppm ASTM D5185m >20	<b>3</b>	2	8

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.4</b>	0.1	0.1
Nitration	Abs/cm *ASTM D7624 >20	<b>6.3</b>	5.2	6.2
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>18.5</b>	17.8	18.9

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.9</b>	13.7	14.6
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.6</b>	9.0	8.8







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.5</b>	14.2	13.5

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0105268  
**Lab Number** : **06102743**  
**Unique Number** : 10900973  
**Test Package** : FLEET

**Received** : 28 Feb 2024  
**Tested** : 29 Feb 2024  
**Diagnosed** : 29 Feb 2024 - Wes Davis

**GFL Environmental - 821 - Ozarks Hauling**  
 33924 Olath Drive  
 Lebanon, MO  
 US 65536

Contact: Landen Johnson  
 landen.johnson@gflenv.com

T: (417)664-0010

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)