



Machine Id  
**OMC SPRINT SH-21 (S/N 20144)**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA 15W40 (--- GAL)**



## DIAGNOSIS

### ▲ Recommendation

We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

### ● Wear

All component wear rates are normal.

### ▲ Contamination

Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0107105</b>	---	---
Sample Date	Client Info	<b>16 Feb 2024</b>	---	---
Machine Age	hrs Client Info	<b>3383</b>	---	---
Oil Age	hrs Client Info	<b>250</b>	---	---
Oil Changed	Client Info	<b>Changed</b>	---	---
Sample Status		<b>ABNORMAL</b>	---	---

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	---	---
Water	WC Method >0.2	<b>NEG</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>89</b>	---	---
Chromium	ppm ASTM D5185m >20	<b>4</b>	---	---
Nickel	ppm ASTM D5185m >4	<b>1</b>	---	---
Titanium	ppm ASTM D5185m	<b>1</b>	---	---
Silver	ppm ASTM D5185m >3	<b>0</b>	---	---
Aluminum	ppm ASTM D5185m >20	<b>12</b>	---	---
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	---	---
Copper	ppm ASTM D5185m >330	<b>19</b>	---	---
Tin	ppm ASTM D5185m >15	<b>&lt;1</b>	---	---
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	---	---
Cadmium	ppm ASTM D5185m	<b>&lt;1</b>	---	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	<b>45</b>	---	---
Barium	ppm ASTM D5185m	<b>2</b>	---	---
Molybdenum	ppm ASTM D5185m	<b>63</b>	---	---
Manganese	ppm ASTM D5185m	<b>2</b>	---	---
Magnesium	ppm ASTM D5185m	<b>547</b>	---	---
Calcium	ppm ASTM D5185m	<b>1450</b>	---	---
Phosphorus	ppm ASTM D5185m	<b>898</b>	---	---
Zinc	ppm ASTM D5185m	<b>1195</b>	---	---
Sulfur	ppm ASTM D5185m	<b>3314</b>	---	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>▲ 37</b>	---	---
Sodium	ppm ASTM D5185m	<b>15</b>	---	---
Potassium	ppm ASTM D5185m >20	<b>15</b>	---	---
Glycol	% *ASTM D2982	<b>NEG</b>	---	---






## INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.1</b>	---	---
Nitration	Abs/cm *ASTM D7624 >20	<b>7.7</b>	---	---
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>18.5</b>	---	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>15.0</b>	---	---
Base Number (BN)	mg KOH/g ASTM D2896	<b>9.2</b>	---	---









# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	13.1	---	---

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0107105      **Received** : 28 Feb 2024  
**Lab Number** : 06102747      **Tested** : 29 Feb 2024  
**Unique Number** : 10900977      **Diagnosed** : 29 Feb 2024 - Don Baldrige  
**Test Package** : MOB 1 ( Additional Tests: Glycol, TBN )

**TRINITAS FARMING**  
 45499 W PANOCHE RD  
 FIREBAUGH, CA  
 US 93622  
 Contact: SPENCER COOPER  
 spencer.cooper@trinitasfarming.com  
 T: (209)493-2999  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)