




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
429048-402450

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0109786	GFL0109843	GFL0109838
Sample Date	Client Info	26 Feb 2024	19 Feb 2024	07 Feb 2024
Machine Age	hrs	17441	19371	17301
Oil Age	hrs	600	600	0
Oil Changed	Client Info	Changed	Changed	Not Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	18	23	10
Chromium	ppm ASTM D5185m >4	2	<1	0
Nickel	ppm ASTM D5185m >2	<1	1	0
Titanium	ppm ASTM D5185m	<1	<1	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >25	3	6	<1
Lead	ppm ASTM D5185m >45	0	<1	0
Copper	ppm ASTM D5185m >85	<1	6	0
Tin	ppm ASTM D5185m >4	<1	<1	0
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	<1	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	8	6	2
Barium	ppm ASTM D5185m 0	0	0	0
Molybdenum	ppm ASTM D5185m 60	64	65	58
Manganese	ppm ASTM D5185m 0	<1	<1	0
Magnesium	ppm ASTM D5185m 1010	921	985	936
Calcium	ppm ASTM D5185m 1070	1210	1161	1175
Phosphorus	ppm ASTM D5185m 1150	972	1087	1039
Zinc	ppm ASTM D5185m 1270	1267	1318	1235
Sulfur	ppm ASTM D5185m 2060	3186	3398	3056

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	5	7	6
Sodium	ppm ASTM D5185m	29	5	3
Potassium	ppm ASTM D5185m >20	2	13	1

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	1.3	0.4	0.4
Nitration	Abs/cm *ASTM D7624 >20	8.5	7.9	8.9
Sulfation	Abs/.1mm *ASTM D7415 >30	21.3	19.1	19.9

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.3	15.7	17.0
Base Number (BN)	mg KOH/g ASTM D2896 9.8	9.0	8.1	7.0







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	14.2	13.9	13.3

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
 Sample No. : GFL0109786
 Lab Number : **06102840**
 Unique Number : 10901070
 Test Package : FLEET

Received : 28 Feb 2024
 Tested : 29 Feb 2024
 Diagnosed : 29 Feb 2024 - Wes Davis

GFL Environmental - 836 - Kansas City Hauling
 7801 East Truman Road
 Kansas City, MO
 US 64126
 Contact: Loyce Stewart
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: