




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**731118**

Component  
**Natural Gas Engine**

Fluid  
**PETRO CANADA DURON GEO LD 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0109794</b>	GFL0103312	GFL0103363
Sample Date	Client Info		<b>27 Feb 2024</b>	23 Jan 2024	20 Dec 2023
Machine Age	hrs	Client Info	<b>6355</b>	6203	6012
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Not Changed</b>	Not Changd	Not Changed
Sample Status			<b>NORMAL</b>	ABNORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.1	<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >50	<b>24</b>	▲ 50	9
Chromium	ppm	ASTM D5185m >4	<b>2</b>	1	<1
Nickel	ppm	ASTM D5185m >2	<b>1</b>	1	0
Titanium	ppm	ASTM D5185m	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >9	<b>3</b>	5	2
Lead	ppm	ASTM D5185m >30	<b>22</b>	2	4
Copper	ppm	ASTM D5185m >35	<b>1</b>	14	1
Tin	ppm	ASTM D5185m >4	<b>2</b>	2	<1
Vanadium	ppm	ASTM D5185m	<b>&lt;1</b>	0	<1
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 50	<b>10</b>	13	17
Barium	ppm	ASTM D5185m 5	<b>0</b>	<1	0
Molybdenum	ppm	ASTM D5185m 50	<b>63</b>	47	52
Manganese	ppm	ASTM D5185m 0	<b>1</b>	11	<1
Magnesium	ppm	ASTM D5185m 560	<b>777</b>	752	545
Calcium	ppm	ASTM D5185m 1510	<b>2224</b>	1323	1493
Phosphorus	ppm	ASTM D5185m 780	<b>907</b>	759	759
Zinc	ppm	ASTM D5185m 870	<b>1347</b>	842	984
Sulfur	ppm	ASTM D5185m 2040	<b>3040</b>	2165	2438

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >+100	<b>6</b>	29	4
Sodium	ppm	ASTM D5185m	<b>8</b>	2	2
Potassium	ppm	ASTM D5185m >20	<b>&lt;1</b>	3	0

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	<b>0</b>	0	0
Nitration	Abs/cm	*ASTM D7624 >20	<b>12.8</b>	11.9	10.7
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>27.3</b>	22.8	21.2

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>21.8</b>	20.2	17.9
Base Number (BN)	mg KOH/g	ASTM D2896 10.2	<b>2.9</b>	4.2	5.1







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.1	14.4	14.3

## GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0109794  
 Lab Number : 06104188  
 Unique Number : 10902418  
 Test Package : FLEET

Received : 29 Feb 2024  
 Tested : 01 Mar 2024  
 Diagnosed : 02 Mar 2024 - Don Baldrige

GFL Environmental - 836 - Kansas City Hauling  
 7801 East Truman Road  
 Kansas City, MO  
 US 64126  
 Contact: Loyce Stewart  
 loyce.stewart@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: