

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id DT796 Component Transmission (Auto) Fluid COGNIS EMGARD 2805 ATF (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.

Fluid Condition

The condition of the fluid is acceptable for the time in service.

SAMPLE INFORM	/ ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0074019	PCA0080981	
Sample Date		Client Info		18 Aug 2023	21 Dec 2022	
Machine Age	mls	Client Info		103036	78459	
Oil Age	mls	Client Info		24577	78459	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				NORMAL	NORMAL	
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	43	84	
Chromium	ppm	ASTM D5185m	>5	0	0	
Nickel	ppm	ASTM D5185m	>5	<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>5	0	0	
Aluminum	ppm	ASTM D5185m	>50	29	50	
Lead	ppm	ASTM D5185m	>50	16	41	
Copper	ppm	ASTM D5185m	>225	19	22	
Tin	ppm	ASTM D5185m	>10	3	6	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		72	86	
Barium	ppm	ASTM D5185m		0	2	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		<1	1	
Magnesium	ppm	ASTM D5185m		0	<1	
Calcium	ppm	ASTM D5185m		103	58	
Phosphorus	ppm	ASTM D5185m		237	253	
Zinc	ppm	ASTM D5185m		0	5	
Sulfur	ppm	ASTM D5185m		1522	928	
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	6	4	
Sodium	ppm	ASTM D5185m		3	2	
Potassium	ppm	ASTM D5185m	>20	<1	4	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	LIGHT	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
6:31:56) Rev: 1					Submitted E	By: Matt Quinlan



OIL ANALYSIS REPORT



	FLUID PROP	ERTIES	method				history2			
	Visc @ 40°C	cSt	ASTM D445	38.9	32.9	34.9				
	SAMPLE IMA	GES	method	limit/base	current	history1	history2			
	Color				no image	no image	no image			
	Bottom				no image	no image	no image			
	20100					g.				
	GRAPHS					1				
	Ferrous Alloys									
	80 - iron									
	70 nickel									
	E.50-									
	40									
	20									
	10									
	\$21/22			18/23						
	ి Non-ferrous Met	als		Au						
	45 copper									
	35 -									
	30	A DESCRIPTION OF THE OWNER OWNER OF THE OWNER OWNER OF THE OWNER								
	E 20		Construction of the Construction							
	15-			and						
	5									
	0			23						
	Dec21			Aug 18.						
	Viscosity @ 40°	C								
	42									
	40 Base									
	00 (00 38									
	3 4-									
	32 - Abpormal									
	30 -									
	28 +			8/23						
	Dec2			Aug1						
ory	: WearCheck USA - 501 Madison Ave., Cary, NC 27513 NW WHITE & CO - GREER DI									
No. nber	: PCA0074019 : 06105650	1060 ROGEF	S BRIDGE RI DUNCAN, S							
mber	: 10903880	Diagr	nosed : 04	Mar 2024 - Se	an Felton	<u> </u>	US 2933			
kage eport.	: FLEE contact Customer Se	rvice at 1-8	300-237-136	9.		Contao mguinlan	ct: Matt Quinlaı @nwwhite.con			
ds that a	are outside of the ISO	17025 scc	pe of accred	litation.		T:	(864)905-850			

 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F:

Page 2 of 2