


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



DT804

Component

Transmission (Auto)

COGNIS EMGARD 2805 ATF (36 QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.

			Nov2022	Aug2023		
SAMPLE INFORM	AOITAN	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0089157	PCA0080484	
Sample Date		Client Info		15 Aug 2023	16 Nov 2022	
Machine Age	mls	Client Info		79620	53294	
Oil Age	mls	Client Info		79620	53294	
Oil Changed		Client Info		Changed	Not Changd	
Sample Status				NORMAL	NORMAL	
CONTAMINATI	ON	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	
WEAR METALS	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>160	83	67	
Chromium	ppm	ASTM D5185m	>5	0	<1	
Nickel	ppm	ASTM D5185m	>5	<1	1	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>5	0	0	
Aluminum	ppm	ASTM D5185m	>50	36	28	
Lead	ppm	ASTM D5185m	>50	45	37	
Copper	ppm		>225	23	16	
Tin	ppm	ASTM D5185m	>10	6	5	
Vanadium	ppm	ASTM D5185m	>10	0	0	
Cadmium		ASTM D5185m		0	0	
	ppm					
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		77	93	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		<1	1	
Manganese	ppm	ASTM D5185m		1	2	
Magnesium	ppm	ASTM D5185m		<1	1	
Calcium	ppm	ASTM D5185m		65	64	
Phosphorus	ppm	ASTM D5185m		259	257	
Zinc	ppm	ASTM D5185m		0	0	
Sulfur	ppm	ASTM D5185m		1167	1320	
CONTAMINAN [*]	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	5	5	
Sodium	ppm	ASTM D5185m		6	5	
Potassium	ppm	ASTM D5185m	>20	3	3	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
:20:14) Dov: 1	Journal	Violai		IILU		Pv: Mott Ouinlo




OIL ANALYSIS REPORT




FLUID PROPI	ERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	38.9	36.1	34.5	
SAMPLE IMA	GES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

GRAPHS



45 T	
40 - copper	大型 医克里克 计分子数字 化丁烷 计分类 医克克氏性 医克克氏性 医克克氏性 医克克氏性 化二甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基甲基
35 - ***********************************	
30	
E 25	
25	
15-	
10	
5	
0	
3/22	//23
lov16/22	ng15/23





Certificate L2367

Laboratory Sample No.

Lab Number : 06105656 Unique Number : 10903886 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : PCA0089157 Received : 29 Feb 2024 **Tested**

: 02 Mar 2024 Diagnosed : 04 Mar 2024 - Sean Felton

NW WHITE & CO - GREER DIVISION 1060 ROGERS BRIDGE RD

DUNCAN, SC US 29334

Contact: Matt Quinlan mquinlan@nwwhite.com T: (864)905-8506

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)