




# OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Machine Id  
**2412 MACK GU713**  
 Component  
**Diesel Engine**  
 Fluid  
**PETRO CANADA DURON SHP 15W40 (48 QTS)**

## DIAGNOSIS

### Recommendation

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. Fuel is present in the oil and is lowering the viscosity. The oil is no longer serviceable due to the presence of contaminants.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>GFL0094658</b>	GFL0103208	GFL0103262
Sample Date	Client Info		<b>28 Feb 2024</b>	20 Dec 2023	06 Dec 2023
Machine Age	hrs	Client Info	<b>29525</b>	29076	28970
Oil Age	hrs	Client Info	<b>0</b>	0	0
Oil Changed	Client Info		<b>Changed</b>	Not Changd	Changed
Sample Status			<b>ABNORMAL</b>	NORMAL	SEVERE

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>6</b>	3	8
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>&lt;1</b>	<1	0
Titanium	ppm	ASTM D5185m >2	<b>0</b>	0	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>2</b>	2	1
Lead	ppm	ASTM D5185m >40	<b>&lt;1</b>	0	0
Copper	ppm	ASTM D5185m >330	<b>3</b>	1	<1
Tin	ppm	ASTM D5185m >15	<b>&lt;1</b>	<1	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	<1	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	<b>2</b>	2	1
Barium	ppm	ASTM D5185m 0	<b>0</b>	0	3
Molybdenum	ppm	ASTM D5185m 60	<b>53</b>	59	58
Manganese	ppm	ASTM D5185m 0	<b>&lt;1</b>	0	0
Magnesium	ppm	ASTM D5185m 1010	<b>824</b>	989	826
Calcium	ppm	ASTM D5185m 1070	<b>923</b>	1082	979
Phosphorus	ppm	ASTM D5185m 1150	<b>858</b>	1118	926
Zinc	ppm	ASTM D5185m 1270	<b>1146</b>	1310	1098
Sulfur	ppm	ASTM D5185m 2060	<b>2724</b>	3448	2961

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>4</b>	5	4
Sodium	ppm	ASTM D5185m	<b>3</b>	2	<1
Potassium	ppm	ASTM D5185m >20	<b>&lt;1</b>	2	2
Fuel	%	ASTM D3524 >3.0	<b>▲ 4.8</b>	2.0	▲ 5.2

## INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.6</b>	0.2	0.8
Nitration	Abs/cm	*ASTM D7624 >20	<b>10.6</b>	6.1	10.0
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>19.8</b>	17.7	19.5


## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>15.9</b>	14.2	15.2
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	<b>5.4</b>	8.9	6.0




# OIL ANALYSIS REPORT


## Fuel Dilution



## Viscosity @ 100°C



## Base Number




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	▲ 12.3	13.9

## GRAPHS


### Ferrous Alloys




### Non-ferrous Metals



## Viscosity @ 100°C



## Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
 Sample No. : GFL0094658  
 Lab Number : 06105840  
 Unique Number : 10909337  
 Test Package : FLEET ( Additional Tests: FuelDilution, PercentFuel )

GFL Environmental - 001 - Raleigh(CNG)

3741 Conquest Drive  
 Garner, NC  
 US 27529

Contact: Craig Johnson  
 craig.johnson@gflenv.com

T: (919)662-7100  
 F: (919)662-7130

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)