


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
VOLVO A40G LB-60 (S/N 340544)
 Component
Drop Box
 Fluid
FLEETLINE 80W90 (2 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0110123	WC0569918	WCM2312772
Sample Date	Client Info		16 Feb 2024	25 Jan 2022	07 May 2021
Machine Age	hrs	Client Info	15391	12269	11265
Oil Age	hrs	Client Info	1590	1362	358
Oil Changed		Client Info	Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	55	68	141
Chromium	ppm	ASTM D5185m >20	<1	1	2
Nickel	ppm	ASTM D5185m >10	<1	0	2
Titanium	ppm	ASTM D5185m	0	<1	0
Silver	ppm	ASTM D5185m	0	4	0
Aluminum	ppm	ASTM D5185m >30	<1	2	8
Lead	ppm	ASTM D5185m >30	0	<1	0
Copper	ppm	ASTM D5185m >30	<1	1	2
Tin	ppm	ASTM D5185m >20	0	0	<1
Antimony	ppm	ASTM D5185m >5	---	0	0
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	41	25	66
Barium	ppm	ASTM D5185m	<1	0	0
Molybdenum	ppm	ASTM D5185m	2	2	<1
Manganese	ppm	ASTM D5185m	<1	<1	1
Magnesium	ppm	ASTM D5185m	57	19	<1
Calcium	ppm	ASTM D5185m	121	457	2
Phosphorus	ppm	ASTM D5185m	716	738	704
Zinc	ppm	ASTM D5185m	98	182	0
Sulfur	ppm	ASTM D5185m	17815	18772	20406


CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >50	13	45	<1
Sodium	ppm	ASTM D5185m	4	10	0
Potassium	ppm	ASTM D5185m >20	7	21	<1

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.76	1.00	2.199

OIL ANALYSIS REPORT




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	MODER
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	LIGHT
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	139	117	157

SAMPLE IMAGES	method	limit/base	current	history1	history2
Color				no image	no image
Bottom				no image	no image

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0110123
Lab Number : **06106763**
Unique Number : 10910260
Test Package : MOB 2
Received : 01 Mar 2024
Tested : 04 Mar 2024
Diagnosed : 06 Mar 2024 - Jonathan Hester

LORUSSO BRISTOL STONE CORP
 611 PLEASANT ST
 WEYMOUTH, MA
 US 02189
 Contact: PAUL MOGAN
 lbstone611@comcast.net
 T: (781)331-5379
 F: (781)337-8274

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)