


OIL ANALYSIS REPORT



NORMAL



Machine Id **326751**

Component **Diesel Engine**

PETRO CANADA DURON SHP 10W30 (--- 0

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Metal levels are typical for a new component breaking in.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. There is no indication of any contamination in the oil.


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

GAL)				Feb2024		
SAMPLE INFOR	RMATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0105602		
Sample Date		Client Info		15 Feb 2024		
Machine Age	mls	Client Info		35888		
Oil Age	mls	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINA	TION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METAI	LS	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	79		
Chromium	ppm	ASTM D5185m	>20	3		
Nickel	ppm	ASTM D5185m	>4	1		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	32		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m	>330	13		
Tin	ppm	ASTM D5185m	>15	2		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	2	10		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	50	72		
Manganese	ppm	ASTM D5185m	0	3		
Magnesium	ppm	ASTM D5185m	950	855		
Calcium	ppm	ASTM D5185m	1050	1133		
Phosphorus	ppm	ASTM D5185m	995	926		
Zinc	ppm	ASTM D5185m	1180	1166		
Sulfur	ppm	ASTM D5185m	2600	3050		
CONTAMINA	NTS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	59		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.7		
Nitration	Abs/cm	*ASTM D7624	>20	11.6		
Sulfation	Abs/.1mm	*ASTM D7415	>30	23.2		
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	19.9		
Base Number (BN)	mg KOH/g	ASTM D2896		6.0		



OIL ANALYSIS REPORT





Visc @ 100°C	cSt	ASTM D445	12.00	10.8	
GRAPHS					
Iron (ppm)				Lead (ppm)	
250 Severe				Severe	
E 150				E 60 Abnormal	
Abnormal				10 7 0	
50				20	
Feb 15/24			Feb15/24	Feb 15/24	Feb15/24
			亞		Ī
Aluminum (ppm)				Chromium (ppm)	
40 - Severe				40 Severe	-
Abnormal				abnormal Abnormal	
10-				10	
0 1 2			24	0 + 52	24
Feb 15/24			Feb15/24	Feb15/24	Feb15/24 ·
Copper (ppm)				Silicon (ppm)	
Severe				80 T Severe	
300				60	
Ē 200 -				Abnormal	
100				20	
Feb15/24			Feb15/24	Feb 15/24	Feb15/24 -
			Feb		是
Viscosity @ 100°C				Base Number	
14 - Abnormal				3)HOX P4 0	
(2001)2 Base		***************************************		<u>a</u> 3.0 +	
10 - Abnormal				Namber (mg KOH(d)	
8				0.0	4
Feb 15/24			Feb15/24	Feb 15/24	Feb15/24 -
_				_	





Certificate L2367

Laboratory Sample No.

Lab Number : 06107204 Unique Number: 10910701

: PCA0105602

Received **Tested** Diagnosed Test Package : MOB 1 (Additional Tests: TBN)

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 04 Mar 2024 : 05 Mar 2024

: 05 Mar 2024 - Wes Davis

VINELAND, NJ Contact: JOHN KEEN jkeen@millertransgroup.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: F: (856)696-5629

MILLER TRUCK LEASING #116

1197 NORTH MAIN ROAD

US 08360