




OIL ANALYSIS REPORT

Sample Rating Trend



WEAR



Machine Id
725014-584

Component
Diesel Engine

Fluid
PETRO CANADA DURON HP 15W40 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. (Customer Sample Comment: A service complete, oil sample only)

Wear

Cylinder, crank, or cam shaft wear is indicated.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0101628	GFL0100043	GFL0062196
Sample Date	Client Info	29 Feb 2024	27 Nov 2023	22 Aug 2023
Machine Age	hrs	10209	9973	153
Oil Age	hrs	236	106	153
Oil Changed	Client Info	Not Chngd	Not Chngd	Not Chngd
Sample Status		ABNORMAL	NORMAL	SEVERE

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<1.0	0.4	▲ 13.5
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	▲ 105	49	▲ 191
Chromium	ppm ASTM D5185m >20	6	4	25
Nickel	ppm ASTM D5185m >4	0	0	<1
Titanium	ppm ASTM D5185m	<1	0	<1
Silver	ppm ASTM D5185m >3	0	0	0
Aluminum	ppm ASTM D5185m >20	10	2	13
Lead	ppm ASTM D5185m >40	9	2	2
Copper	ppm ASTM D5185m >330	3	1	4
Tin	ppm ASTM D5185m >15	<1	<1	<1
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	4	6	3
Barium	ppm ASTM D5185m	0	0	0
Molybdenum	ppm ASTM D5185m	69	66	56
Manganese	ppm ASTM D5185m	<1	<1	2
Magnesium	ppm ASTM D5185m	1134	955	883
Calcium	ppm ASTM D5185m	1566	1214	992
Phosphorus	ppm ASTM D5185m	1222	1056	906
Zinc	ppm ASTM D5185m	1505	1245	1119
Sulfur	ppm ASTM D5185m	3347	2752	2987

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	8	6	12
Sodium	ppm ASTM D5185m	4	5	6
Potassium	ppm ASTM D5185m >20	<1	0	0

INFRA-RED

method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	2.9	1.7	▲ 6.7
Nitration	Abs/cm *ASTM D7624 >20	12.2	9.7	27.1
Sulfation	Abs/.1mm *ASTM D7415 >30	25.5	21.1	51.4


FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	18.5	16.1	60.5
Base Number (BN)	mg KOH/g ASTM D2896 9.8	7.8	8.2	▲ 0.0




OIL ANALYSIS REPORT


▲ Ferrous Alloys



Base Number



Viscosity @ 100°C




VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG


FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.6	15.0	14.2

GRAPHS


▲ Ferrous Alloys




Non-ferrous Metals



Viscosity @ 100°C



Base Number



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0101628
Lab Number : 06107962
Unique Number : 10911459
Test Package : FLEET

Received : 04 Mar 2024
Tested : 05 Mar 2024
Diagnosed : 06 Mar 2024 - Jonathan Hester

GFL Environmental - 626 - Cadillac Hauling
 1501 Ron Wilson St
 Cadillac, MI
 US 49601
 Contact: GARY BREWER
 gbrewerjr@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: