




OIL ANALYSIS REPORT

Sample Rating Trend



FUEL



Machine Id
8994
Component
Diesel Engine
Fluid
PETRO CANADA DURON SHP 15W40 (--- LTR)

DIAGNOSIS

Recommendation

The oil change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of fuel present in the oil. Tests confirm the presence of fuel in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The oil is no longer serviceable due to the presence of contaminants.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		GFL0112985	GFL0089488	GFL0089477
Sample Date	Client Info		28 Feb 2024	31 Aug 2023	20 Jul 2023
Machine Age	hrs	Client Info	20329	20002	19875
Oil Age	hrs	Client Info	20329	0	0
Oil Changed	Client Info		Changed	Changed	N/A
Sample Status			ABNORMAL	SEVERE	SEVERE

CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>75	20	14	54
Chromium	ppm	ASTM D5185m	>5	1	<1	3
Nickel	ppm	ASTM D5185m	>4	<1	0	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>15	5	2	12
Lead	ppm	ASTM D5185m	>25	<1	<1	1
Copper	ppm	ASTM D5185m	>100	<1	2	<1
Tin	ppm	ASTM D5185m	>4	<1	<1	<1
Antimony	ppm	ASTM D5185m		---	---	---
Vanadium	ppm	ASTM D5185m		0	0	0
Beryllium	ppm	ASTM D5185m		---	---	---
Cadmium	ppm	ASTM D5185m		0	0	0

ADDITIVES

	method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	2	2	0
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	60	58	54	51
Manganese	ppm	ASTM D5185m	0	<1	1	<1
Magnesium	ppm	ASTM D5185m	1010	933	898	911
Calcium	ppm	ASTM D5185m	1070	1026	986	902
Phosphorus	ppm	ASTM D5185m	1150	987	969	895
Zinc	ppm	ASTM D5185m	1270	1185	1159	1119
Sulfur	ppm	ASTM D5185m	2060	2938	3357	2976
Lithium	ppm	ASTM D5185m		---	---	---

CONTAMINANTS



	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	5	4	8
Sodium	ppm	ASTM D5185m		5	7	6
Potassium	ppm	ASTM D5185m	>20	6	7	14
Fuel	%	ASTM D3524	>3.0	▲ 4.5	▲ 12.9	▲ 22.7

INFRA-RED

	method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>6	0.7	0.4	2.9
Nitration	Abs/cm	*ASTM D7624	>20	9.4	10.0	16.0
Sulfation	Abs.1mm	*ASTM D7415	>30	20.0	23.6	28.1



OIL ANALYSIS REPORT







FLUID DEGRADATION	method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414	>25	17.2	18.0	24.9
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.3	8.9	6.1

VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	12.9	▲ 11.9	▲ 10.2

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0112985 **Received** : 06 Mar 2024
Lab Number : 06109996 **Tested** : 08 Mar 2024
Unique Number : 10913493 **Diagnosed** : 08 Mar 2024 - Wes Davis
Test Package : FLEET (Additional Tests: PercentFuel)

GFL Environmental - 918 - Hartland HC
 630 E Industrial Drive
 Hartland, WI
 US 53029
 Contact: David McCall
 david.mccall@gflenv.com
 T: (262)369-3069
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)