




Machine Id  
**CELL 3 AUGER CART**  
 Component  
**Gearbox**  
 Fluid  
**MOBIL SHC CIBUS 460 (--- QTS)**



## DIAGNOSIS

**Recommendation**  
 No corrective action is recommended at this time. Resample at the next service interval to monitor.

**Wear**  
 All component wear rates are normal.

**Contamination**  
 There is a high amount of silt (particulates < 6 microns in size) present in the oil.

**Fluid Condition**  
 The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>PCA0113544</b>	PCA0099612	PCA0078701
Sample Date	Client Info	<b>24 Feb 2024</b>	28 Aug 2023	27 Aug 2022
Machine Age	hrs	Client Info	0	0
Oil Age	hrs	Client Info	0	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>ABNORMAL</b>	ABNORMAL	ABNORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >200	<b>11</b>	12	12
Chromium	ppm ASTM D5185m >15	<b>0</b>	0	0
Nickel	ppm ASTM D5185m >15	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >25	<b>0</b>	0	<1
Lead	ppm ASTM D5185m >100	<b>0</b>	0	0
Copper	ppm ASTM D5185m >200	<b>0</b>	0	0
Tin	ppm ASTM D5185m >25	<b>&lt;1</b>	0	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	<b>32</b>	41	45
Barium	ppm ASTM D5185m	<b>0</b>	2	0
Molybdenum	ppm ASTM D5185m	<b>0</b>	0	0
Manganese	ppm ASTM D5185m	<b>0</b>	<1	0
Magnesium	ppm ASTM D5185m	<b>&lt;1</b>	1	<1
Calcium	ppm ASTM D5185m	<b>582</b>	596	642
Phosphorus	ppm ASTM D5185m	<b>535</b>	510	510
Zinc	ppm ASTM D5185m	<b>14</b>	23	14
Sulfur	ppm ASTM D5185m	<b>646</b>	696	572

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >50	<b>2</b>	3	2
Sodium	ppm ASTM D5185m	<b>&lt;1</b>	0	<1
Potassium	ppm ASTM D5185m >20	<b>0</b>	1	0





## FLUID CLEANLINESS

method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647 >10000	<b>▲ 25020</b>	▲ 28358	▲ 185535
Particles >6µm	ASTM D7647 >2500	<b>419</b>	593	▲ 22271
Particles >14µm	ASTM D7647 >640	<b>12</b>	33	169
Particles >21µm	ASTM D7647 >160	<b>4</b>	9	19
Particles >38µm	ASTM D7647 >40	<b>1</b>	1	0
Particles >71µm	ASTM D7647 >10	<b>0</b>	1	0
Oil Cleanliness	ISO 4406 (c) >20/18/16	<b>▲ 22/16/11</b>	▲ 22/16/12	▲ 25/22/15

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g ASTM D8045	<b>0.06</b>	0.16	0.14


# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	458	437	438

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0113544 **Received** : 06 Mar 2024  
**Lab Number** : **06110152** **Tested** : 07 Mar 2024  
**Unique Number** : 10913649 **Diagnosed** : 07 Mar 2024 - Doug Bogart  
**Test Package** : IND 2 ( Additional Tests: PrtCount )

**KraftHeinz - New Ulm - Plant 8302**  
 2525 S BRIDGE STREET  
 NEW ULM, MN  
 US 56073  
 Contact: RYAN SCHMID  
 ryan.schmid@kraftheinz.com  
 T: (507)568-0338  
 F: (507)354-7927

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)