


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 10460 Component

Diesel Engine

PETRO CANADA DURON SHP 15W40 (7 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition


The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

Q2017 Mey2018 Apr2019 Mer2020 Octd020 Jun2021 Med0023 Ove2023							
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2	
Sample Number		Client Info		GFL0068842	GFL0068896	GFL0097164	
Sample Date		Client Info		01 Mar 2024	19 Feb 2024	29 Jan 2024	
Machine Age	hrs	Client Info		7603	7467	7352	
Oil Age	hrs	Client Info		0	7467	0	
Oil Changed		Client Info		Changed	Not Changd	Not Changd	
Sample Status				NORMAL	NORMAL	NORMAL	
CONTAMINAT	ION	method	limit/base	current	history1	history2	
Fuel		WC Method	>3.0	<1.0	<1.0	<1.0	
Water		WC Method	>0.2	NEG	NEG	NEG	
Glycol		WC Method		NEG	NEG	NEG	
WEAR METAL	S	method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>75	3	20	5	
Chromium	ppm	ASTM D5185m	>5	0	<1	0	
Nickel	ppm	ASTM D5185m	>4	0	0	0	
Titanium	ppm	ASTM D5185m	>2	0	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	0	
Aluminum	ppm	ASTM D5185m	>15	1	4	1	
Lead	ppm	ASTM D5185m	>25	0	0	<1	
Copper	ppm	ASTM D5185m	>100	<1	<1	0	
Tin	ppm	ASTM D5185m	>4	0	<1	<1	
Vanadium	ppm	ASTM D5185m		<1	0	0	
Cadmium	ppm	ASTM D5185m		0	0	0	
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m	0	8	5	6	
Barium	ppm	ASTM D5185m	0	0	0	0	
Molybdenum	ppm	ASTM D5185m	60	57	56	53	
Manganese	ppm	ASTM D5185m	0	0	<1	0	
Magnesium	ppm	ASTM D5185m	1010	942	948	900	
Calcium	ppm	ASTM D5185m	1070	1025	986	919	
Phosphorus	ppm	ASTM D5185m	1150	992	1031	989	
Zinc	ppm	ASTM D5185m	1270	1146	1261	1193	
Sulfur	ppm	ASTM D5185m	2060	3180	3129	3131	
CONTAMINAN	ITS	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	2	6	3	
Sodium	ppm	ASTM D5185m		1	3	<1	
Potassium	ppm	ASTM D5185m	>20	<1	3	2	
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>6	0.1	0.5	0.6	
Nitration	Abs/cm	*ASTM D7624	>20	4.5	6.1	5.0	
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.2	18.2	17.8	
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	12.6	13.0	12.2	
Base Number (BN)	mg KOH/g	ASTM D2896	9.8	8.9	8.5	9.0	



OIL ANALYSIS REPORT








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG


FLUID PROPI	ERTIES	method				history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.6	13.8	13.8

GRAPHS













Certificate L2367

Laboratory Sample No.

: GFL0068842 Lab Number : 06111038 Unique Number : 10914535 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 07 Mar 2024 **Tested**

: 07 Mar 2024 Diagnosed : 07 Mar 2024 - Wes Davis

GFL Environmental - 073 - Warner Robins - Transwaste

155 Story Road Warner Robins, GA US 31093

Contact: JOSH MALONEY

jmaloney@gflenv.com T:

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: