




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**718002**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0111106</b>	GFL0111083	GFL06074303
Sample Date	Client Info	<b>26 Feb 2024</b>	07 Feb 2024	29 Jan 2024
Machine Age	hrs	<b>9306</b>	9173	0
Oil Age	hrs	<b>684</b>	551	0
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	<b>6</b>	3	11
Chromium	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	<1
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >25	<b>2</b>	2	4
Lead	ppm ASTM D5185m >45	<b>0</b>	<1	0
Copper	ppm ASTM D5185m >85	<b>&lt;1</b>	0	<1
Tin	ppm ASTM D5185m >4	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>13</b>	17	17
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>79</b>	82	87
Manganese	ppm ASTM D5185m 0	<b>0</b>	0	<1
Magnesium	ppm ASTM D5185m 1010	<b>883</b>	944	887
Calcium	ppm ASTM D5185m 1070	<b>1065</b>	1144	1017
Phosphorus	ppm ASTM D5185m 1150	<b>984</b>	1049	954
Zinc	ppm ASTM D5185m 1270	<b>1179</b>	1211	1213
Sulfur	ppm ASTM D5185m 2060	<b>3161</b>	3157	2795

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	<b>3</b>	2	3
Sodium	ppm ASTM D5185m	<b>3</b>	2	4
Potassium	ppm ASTM D5185m >20	<b>8</b>	6	10

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.2</b>	0.1	0.3
Nitration	Abs/cm *ASTM D7624 >20	<b>6.0</b>	5.1	7.9
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.5</b>	17.4	19.0

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>13.5</b>	12.8	15.0
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.3</b>	8.6	8.0







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.6</b>	13.8	13.4

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0111106 **Received** : 07 Mar 2024  
**Lab Number** : **06111148** **Tested** : 07 Mar 2024  
**Unique Number** : 10914645 **Diagnosed** : 07 Mar 2024 - Wes Davis  
**Test Package** : FLEET

**GFL environmental - 867 - Trafford (Blount Hauling)**  
 1130 County Line Rd  
 Trafford, AL  
 US 35172  
 Contact: Jonathan Williams  
 jonathan.williams@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)