




# OIL ANALYSIS REPORT

Sample Rating Trend



DIRT



Area  
**(BC71121)**  
Machine Id  
**4593M**

Component  
**Diesel Engine**  
Fluid

**PETRO CANADA DURON SHP 15W40 (5 GAL)**

## DIAGNOSIS

### Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. Oil and filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

### Wear

All component wear rates are normal.

### Contamination

Sodium and/or potassium levels are high. Elemental level of silicon (Si) above normal indicating ingress of seal material.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0106709</b>	GFL0091469	GFL0081314
Sample Date	Client Info	<b>20 Feb 2024</b>	18 Sep 2023	15 May 2023
Machine Age	hrs	<b>7188</b>	6259	5953
Oil Age	hrs	<b>600</b>	600	600
Oil Changed	Client Info	<b>Changed</b>	N/A	Changed
Sample Status		<b>ABNORMAL</b>	ABNORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>62</b>	45	91
Chromium	ppm ASTM D5185m >20	<b>3</b>	4	3
Nickel	ppm ASTM D5185m >4	<b>1</b>	1	2
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>6</b>	9	8
Lead	ppm ASTM D5185m >40	<b>&lt;1</b>	0	4
Copper	ppm ASTM D5185m >330	<b>20</b>	1	32
Tin	ppm ASTM D5185m >15	<b>0</b>	<1	<1
Vanadium	ppm ASTM D5185m	<b>&lt;1</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>62</b>	4	5
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>136</b>	65	71
Manganese	ppm ASTM D5185m 0	<b>1</b>	<1	1
Magnesium	ppm ASTM D5185m 1010	<b>1076</b>	1004	944
Calcium	ppm ASTM D5185m 1070	<b>1259</b>	1144	1124
Phosphorus	ppm ASTM D5185m 1150	<b>1093</b>	1094	993
Zinc	ppm ASTM D5185m 1270	<b>1385</b>	1325	1291
Sulfur	ppm ASTM D5185m 2060	<b>3117</b>	4048	2564

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>▲ 43</b>	▲ 26	15
Sodium	ppm ASTM D5185m	<b>▲ 2025</b>	135	177
Potassium	ppm ASTM D5185m >20	<b>▲ 17</b>	10	4
Glycol	% *ASTM D2982	<b>NEG</b>	NEG	NEG

## INFRA-RED





method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.5</b>	0.2	1.6
Nitration	Abs/cm *ASTM D7624 >20	<b>18.4</b>	6.2	16.6
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>26.1</b>	17.7	29.7

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>21.0</b>	12.9	31.1
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>11.6</b>	9.0	6.1







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>15.6</b>	13.8	14.1

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0106709 **Received** : 07 Mar 2024  
**Lab Number** : 06111274 **Tested** : 11 Mar 2024  
**Unique Number** : 10914771 **Diagnosed** : 11 Mar 2024 - Jonathan Hester  
**Test Package** : FLEET ( Additional Tests: Glycol )

**GFL Environmental - 405 - Arbor Hills**  
 7400 Napier Rd  
 NORTHVILLE, MI  
 US 48168  
 Contact: Anthony Hopkins  
 ahopkins@gflenv.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: