


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



SC-10 (S/N D-1184)

Screw Compressor

CHEVRON REFRIGERATION OIL WF 68 (---

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

The water content is negligible. There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

- GAL)		Jan 2023	May2023	Jul2023 Oet2023	Feb 2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		PCA0115282	PCA0106633	PCA0101708
Sample Date		Client Info		23 Feb 2024	09 Oct 2023	26 Jul 2023
Machine Age	hrs	Client Info		11638	9205	74897
Oil Age	hrs	Client Info		7570	5139	3425
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METAL	S	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>60	10	4	6
Chromium	ppm	ASTM D5185m	>4	0	0	0
Nickel	ppm	ASTM D5185m		0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>5	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>30	0	0	<1
Tin	ppm	ASTM D5185m	>15	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	1	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		0	2	0
Calcium	ppm	ASTM D5185m		0	0	5
Phosphorus	ppm	ASTM D5185m		0	0	0
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		186	192	199
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1	0	<1
Sodium	ppm	ASTM D5185m		0	<1	<1
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.1	0.006	0.003	0.00
ppm Water	ppm	ASTM D6304	>1000	65	29.9	0.00
FLUID CLEANL	LINESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>10000	9641	9518	<u>\$\text{23577}\$</u>
Particles >6µm		ASTM D7647	>2500	2164	1745	△ 6329
Particles >14μm		ASTM D7647	>320	13	69	239
Particles >21μm		ASTM D7647		1	17	40
Particles >38μm		ASTM D7647	>20	0	1	0
Particles >71μm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/18/15	20/18/11	20/18/13	<u>22/20/15</u>
FLUID DEGRAD	OITAC		limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.014	0.014	0.015



OIL ANALYSIS REPORT

