




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Area
(YA122710)

Machine Id
3633C

Component
Natural Gas Engine

Fluid
PETRO CANADA DURON GEO LD 15W40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0109754	GFL0092698	GFL0072363
Sample Date	Client Info	06 Mar 2024	03 Oct 2023	25 Jan 2023
Machine Age	hrs	0	20118	20118
Oil Age	hrs	0	252	20118
Oil Changed	Client Info	N/A	Not Changd	Not Changd
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Water	WC Method >0.1	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >50	8	3	11
Chromium	ppm ASTM D5185m >4	<1	2	2
Nickel	ppm ASTM D5185m >2	<1	<1	0
Titanium	ppm ASTM D5185m	<1	<1	0
Silver	ppm ASTM D5185m >3	<1	0	0
Aluminum	ppm ASTM D5185m >9	2	2	2
Lead	ppm ASTM D5185m >30	<1	0	1
Copper	ppm ASTM D5185m >35	3	<1	7
Tin	ppm ASTM D5185m >4	<1	<1	<1
Antimony	ppm ASTM D5185m	---	---	---
Vanadium	ppm ASTM D5185m	<1	<1	0
Cadmium	ppm ASTM D5185m	<1	<1	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 50	54	26	36
Barium	ppm ASTM D5185m 5	0	10	0
Molybdenum	ppm ASTM D5185m 50	47	53	49
Manganese	ppm ASTM D5185m 0	<1	0	<1
Magnesium	ppm ASTM D5185m 560	524	736	557
Calcium	ppm ASTM D5185m 1510	1421	1076	1403
Phosphorus	ppm ASTM D5185m 780	694	907	747
Zinc	ppm ASTM D5185m 870	827	1021	882
Sulfur	ppm ASTM D5185m 2040	2389	2836	2857

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >+100	12	3	7
Sodium	ppm ASTM D5185m	4	2	6
Potassium	ppm ASTM D5185m >20	2	<1	0

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	0.1	0	0.1
Nitration	Abs/cm *ASTM D7624 >20	6.3	4.6	6.9
Sulfation	Abs/.1mm *ASTM D7415 >30	17.6	16.7	18.2

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.0	12.7	14.5
Base Number (BN)	mg KOH/g ASTM D2896 10.2	9.3	8.9	8.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.1	14.8	14.2	13.9

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0109754 **Received** : 08 Mar 2024
Lab Number : **06113482** **Tested** : 11 Mar 2024
Unique Number : 10916979 **Diagnosed** : 11 Mar 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 005 - Wilson/Tri-East(CNG)
 2810 Contentnea Road S
 Wilson, NC
 US 27893-8501
 Contact: SPENCER LIGGON
 spencer.liggon@gflenv.com
 T: (800)207-6618
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)