




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**212018**  
Component  
**Diesel Engine**  
Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0105238</b>	GFL0105179	GFL0105131
Sample Date	Client Info	<b>06 Mar 2024</b>	02 Feb 2024	09 Jan 2024
Machine Age	hrs	<b>4291</b>	4110	3970
Oil Age	hrs	<b>150</b>	150	150
Oil Changed	Client Info	<b>Not Changed</b>	Not Changed	Not Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >80	<b>0</b>	<1	<1
Chromium	ppm ASTM D5185m >5	<b>0</b>	0	<1
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	0	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >30	<b>0</b>	1	2
Lead	ppm ASTM D5185m >30	<b>0</b>	<1	0
Copper	ppm ASTM D5185m >150	<b>0</b>	<1	0
Tin	ppm ASTM D5185m >5	<b>0</b>	0	0
Vanadium	ppm ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>0</b>	0	1
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>55</b>	56	63
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	0
Magnesium	ppm ASTM D5185m 1010	<b>895</b>	937	1059
Calcium	ppm ASTM D5185m 1070	<b>968</b>	1005	1160
Phosphorus	ppm ASTM D5185m 1150	<b>902</b>	1017	1181
Zinc	ppm ASTM D5185m 1270	<b>1084</b>	1227	1304
Sulfur	ppm ASTM D5185m 2060	<b>2853</b>	3176	3959

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >20	<b>4</b>	5	6
Sodium	ppm ASTM D5185m	<b>&lt;1</b>	1	<1
Potassium	ppm ASTM D5185m >20	<b>0</b>	3	1

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0</b>	0	0
Nitration	Abs/cm *ASTM D7624 >20	<b>4.0</b>	4.0	4.0
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>17.1</b>	17.3	17.2

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>12.8</b>	12.7	12.8
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.9</b>	9.0	9.1







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>14.6</b>	14.6	14.6

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0105238 **Received** : 11 Mar 2024  
**Lab Number** : **06113824** **Tested** : 11 Mar 2024  
**Unique Number** : 10922657 **Diagnosed** : 11 Mar 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 821 - Ozarks Hauling**  
 33924 Olath Drive  
 Lebanon, MO  
 US 65536  
 Contact: Landen Johnson  
 landen.johnson@gflenv.com  
 T: (417)664-0010  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)