




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Area  
**{UNASSIGNED}**

Machine Id  
**512014**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0061035</b>	GFL0099625	GFL0030393
Sample Date	Client Info	<b>05 Mar 2024</b>	14 Nov 2023	05 Jun 2023
Machine Age	hrs	<b>4400</b>	3756	3013
Oil Age	hrs	<b>590</b>	615	613
Oil Changed	Client Info	<b>Changed</b>	Changed	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >100	<b>17</b>	23	23
Chromium	ppm ASTM D5185m >20	<b>&lt;1</b>	1	1
Nickel	ppm ASTM D5185m >4	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>0</b>	<1	0
Silver	ppm ASTM D5185m >3	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >20	<b>3</b>	6	4
Lead	ppm ASTM D5185m >40	<b>0</b>	1	1
Copper	ppm ASTM D5185m >330	<b>&lt;1</b>	2	1
Tin	ppm ASTM D5185m >15	<b>0</b>	<1	1
Vanadium	ppm ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>8</b>	4	8
Barium	ppm ASTM D5185m 0	<b>0</b>	0	0
Molybdenum	ppm ASTM D5185m 60	<b>62</b>	64	68
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>923</b>	971	960
Calcium	ppm ASTM D5185m 1070	<b>1111</b>	1104	1136
Phosphorus	ppm ASTM D5185m 1150	<b>1020</b>	962	1037
Zinc	ppm ASTM D5185m 1270	<b>1182</b>	1267	1303
Sulfur	ppm ASTM D5185m 2060	<b>3157</b>	2750	3487

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >25	<b>3</b>	5	5
Sodium	ppm ASTM D5185m	<b>2</b>	2	<1
Potassium	ppm ASTM D5185m >20	<b>5</b>	13	10

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.7</b>	0.9	0.7
Nitration	Abs/cm *ASTM D7624 >20	<b>9.5</b>	10.8	9.6
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>20.6</b>	22.2	21.5

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>16.8</b>	18.2	17.0
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>7.3</b>	7.2	7.9







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.0</b>	13.5	13.1

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0061035      **Received** : 12 Mar 2024  
**Lab Number** : **06115661**      **Tested** : 13 Mar 2024  
**Unique Number** : 10924494      **Diagnosed** : 13 Mar 2024 - Wes Davis  
**Test Package** : FLEET

**GFL Environmental - 633 - Grand Haven**  
 1680 Peach St  
 Whitehall, MI  
 US 49461  
 Contact: Derek Kater  
 dkater@gflenv.com  
 T:  
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)