

## **OIL ANALYSIS REPORT**

Sample Rating Trend

WEAR



Machine Id WL0097-1321 Component

Diesel Engine

CHEVRON DELO 400 XLE 15W40 (--- GAL)

DIAGNOSIS	

## Recommendation

No corrective action is recommended at this time. We recommend an early resample to monitor this condition. Note that there appears to be a discrepancy in the total time on this component, when compared to the historical data.

## 🔺 Wear

The aluminum level is abnormal. Piston, ring and cylinder wear is indicated.

#### Contamination

There is no indication of any contamination in the oil.

## Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.

(LE 15W40 ( 0	GAL)	Feb2021	Лау2021 Aug2021 Oct20	21 Feb2023 May2023 Oct2023	Mar2024	
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		GFL0104662	GFL0096256	GFL0064494
Sample Date		Client Info		07 Mar 2024	19 Oct 2023	23 May 2023
Machine Age	hrs	Client Info		10132	11386	10085
Dil Age	hrs	Client Info		0	0	0
Dil Changed		Client Info		N/A	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
CONTAMINAT	ION	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0	<1.0	<1.0
Vater		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method		NEG	NEG	NEG
WEAR METAL	S	method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>100	33	47	22
Chromium	ppm	ASTM D5185m	>20	3	4	2
Nickel	ppm	ASTM D5185m	>2	0	<1	<1
Titanium	ppm	ASTM D5185m	>2	10	5	10
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	<u> </u>	<b>6</b> 6	<b>4</b> 7
ead	ppm	ASTM D5185m	>40	0	0	1
Copper	ppm	ASTM D5185m	>330	3	11	27
īn	ppm	ASTM D5185m	>15	0	<1	<1
/anadium	ppm	ASTM D5185m		0	<1	<1
Cadmium	ppm	ASTM D5185m		0	<1	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		75	52	73
Barium	ppm	ASTM D5185m		0	0	0
/lolybdenum	ppm	ASTM D5185m		56	93	58
Manganese	ppm	ASTM D5185m		<1	<1	1
/lagnesium	ppm	ASTM D5185m		691	631	651
Calcium	ppm	ASTM D5185m		1508	1415	1507
Phosphorus	ppm	ASTM D5185m	760	668	649	682
Zinc	ppm	ASTM D5185m	830	799	778	809
Sulfur	ppm	ASTM D5185m	2770	3225	3192	3489
CONTAMINAN	TS	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	7	10	7
Sodium	ppm	ASTM D5185m		21	41	40
Potassium	ppm	ASTM D5185m	>20	8	16	16
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.6	1	0.6
Nitration	Abs/cm	*ASTM D7624	>20	10.5	11.4	10.6
Sulfation	Abs/.1mm	*ASTM D7415	>30	22.2	25.8	22.9
FLUID DEGRA	DATION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	18.6	22.2	18.5
Base Number (BN)	mg KOH/a	ASTM D2896	10.7	5.9	6.0	6.5
( -)	0			-		

Page 1 of 2



Feb23/21

Vlav4/21

Aug25/21.

0ct28/21

Feb3/23

/av23/23

# **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	nistory i	nistory2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPE	RTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14.9	13.8	13.9	13.8
GRAPHS						

Ferrous Alloys

50



Certificate 12367 Test Package : FLEET To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Submitted By: KEITH CAMPBELL

andyg@americanwaste.org

T: (989)370-2941

F: