




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
224030-632104

Component
Gasoline Engine

Fluid
RIDGELINE SYNTHETIC BLEND 5W-20 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	GFL0101899	GFL0101989	GFL0101955
Sample Date	Client Info	12 Mar 2024	13 Feb 2024	22 Dec 2023
Machine Age	mls Client Info	199609	197637	194704
Oil Age	mls Client Info	4905	2933	4478
Oil Changed	Client Info	Not Chngd	Not Chngd	Changed
Sample Status		NORMAL	NORMAL	NORMAL

CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >4.0	<1.0	<1.0	<1.0
Water	WC Method >0.2	NEG	NEG	NEG
Glycol	WC Method	NEG	NEG	NEG

WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >150	30	24	28
Chromium	ppm ASTM D5185m >20	2	1	1
Nickel	ppm ASTM D5185m >5	<1	0	0
Titanium	ppm ASTM D5185m	<1	<1	0
Silver	ppm ASTM D5185m >2	0	0	0
Aluminum	ppm ASTM D5185m >40	6	5	6
Lead	ppm ASTM D5185m >50	0	0	<1
Copper	ppm ASTM D5185m >155	2	2	2
Tin	ppm ASTM D5185m >10	0	<1	0
Vanadium	ppm ASTM D5185m	0	0	0
Cadmium	ppm ASTM D5185m	0	0	0

ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m	14	27	9
Barium	ppm ASTM D5185m	0	0	1
Molybdenum	ppm ASTM D5185m 79	95	96	53
Manganese	ppm ASTM D5185m	<1	<1	1
Magnesium	ppm ASTM D5185m 590	493	410	284
Calcium	ppm ASTM D5185m 990	1193	1168	755
Phosphorus	ppm ASTM D5185m 770	667	599	358
Zinc	ppm ASTM D5185m 850	827	708	437
Sulfur	ppm ASTM D5185m 3000	2309	2167	1416

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	19	16	22
Sodium	ppm ASTM D5185m >400	4	5	8
Potassium	ppm ASTM D5185m >20	6	4	17

INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844	0.1	0	0
Nitration	Abs/cm *ASTM D7624 >20	10.3	9.2	11.3
Sulfation	Abs/.1mm *ASTM D7415 >30	22.1	19.8	23.3

FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	15.3	12.1	15.5
Base Number (BN)	mg KOH/g ASTM D2896 7	5.6	4.6	4.7







OIL ANALYSIS REPORT



PARAMETER	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	8.9	9.4	8

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : GFL0101899 **Received** : 13 Mar 2024
Lab Number : 06116959 **Tested** : 14 Mar 2024
Unique Number : 10925792 **Diagnosed** : 14 Mar 2024 - Wes Davis
Test Package : FLEET

GFL Environmental - 894 - Ada Hauling
 1904 North Broadway, Suite D
 Ada, OK
 US 74820
 Contact: Johnny Spurlock
 jspurlock@gflenv.com
 T: (405)664-4476
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)