




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**712028**

Component  
**Diesel Engine**

Fluid  
**PETRO CANADA DURON SHP 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>GFL0101900</b>	GFL0101973	GFL0078382
Sample Date	Client Info	<b>12 Mar 2024</b>	28 Dec 2023	14 Nov 2023
Machine Age	hrs	<b>2516</b>	2323	2175
Oil Age	hrs	<b>341</b>	148	550
Oil Changed	Client Info	<b>Not Changed</b>	Not Changd	Changed
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >5	<b>&lt;1.0</b>	<1.0	<1.0
Water	WC Method >0.2	<b>NEG</b>	NEG	NEG
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2
Iron	ppm ASTM D5185m >110	<b>7</b>	5	13
Chromium	ppm ASTM D5185m >4	<b>&lt;1</b>	<1	<1
Nickel	ppm ASTM D5185m >2	<b>0</b>	0	0
Titanium	ppm ASTM D5185m	<b>&lt;1</b>	<1	<1
Silver	ppm ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm ASTM D5185m >25	<b>5</b>	4	8
Lead	ppm ASTM D5185m >45	<b>0</b>	<1	0
Copper	ppm ASTM D5185m >85	<b>&lt;1</b>	<1	1
Tin	ppm ASTM D5185m >4	<b>&lt;1</b>	1	0
Vanadium	ppm ASTM D5185m	<b>0</b>	0	<1
Cadmium	ppm ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

method	limit/base	current	history1	history2
Boron	ppm ASTM D5185m 0	<b>2</b>	4	2
Barium	ppm ASTM D5185m 0	<b>0</b>	0	<1
Molybdenum	ppm ASTM D5185m 60	<b>61</b>	60	62
Manganese	ppm ASTM D5185m 0	<b>0</b>	<1	<1
Magnesium	ppm ASTM D5185m 1010	<b>921</b>	1034	963
Calcium	ppm ASTM D5185m 1070	<b>1083</b>	1145	1078
Phosphorus	ppm ASTM D5185m 1150	<b>996</b>	1127	1009
Zinc	ppm ASTM D5185m 1270	<b>1223</b>	1295	1263
Sulfur	ppm ASTM D5185m 2060	<b>3154</b>	3392	3001

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon	ppm ASTM D5185m >30	<b>5</b>	3	4
Sodium	ppm ASTM D5185m	<b>2</b>	2	6
Potassium	ppm ASTM D5185m >20	<b>10</b>	4	17

## INFRA-RED



method	limit/base	current	history1	history2
Soot %	% *ASTM D7844 >3	<b>0.2</b>	0.1	0.2
Nitration	Abs/cm *ASTM D7624 >20	<b>6.6</b>	5.6	8.5
Sulfation	Abs/.1mm *ASTM D7415 >30	<b>18.3</b>	17.7	19.9

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Oxidation	Abs/.1mm *ASTM D7414 >25	<b>14.7</b>	13.9	16.9
Base Number (BN)	mg KOH/g ASTM D2896 9.8	<b>8.2</b>	8.5	7.5







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	15.4	<b>13.3</b>	13.7	12.6

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : GFL0101900  
**Lab Number** : 06116961  
**Unique Number** : 10925794  
**Test Package** : FLEET

**Received** : 13 Mar 2024  
**Tested** : 14 Mar 2024  
**Diagnosed** : 14 Mar 2024 - Wes Davis

**GFL Environmental - 894 - Ada Hauling**  
 1904 North Broadway, Suite D  
 Ada, OK  
 US 74820

Contact: Johnny Spurlock  
 jspurlock@gflenv.com

T: (405)664-4476

F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)