


OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
398277

Component
Diesel Engine

Fluid
PETRO CANADA DURON SHP 10W30 (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		PCA0099006	PCA0001107	---
Sample Date	Client Info		15 Nov 2023	25 May 2019	---
Machine Age	mls	Client Info	304914	26977	---
Oil Age	mls	Client Info	0	9089	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			NORMAL	NORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	11	25	---
Chromium	ppm	ASTM D5185m >20	<1	<1	---
Nickel	ppm	ASTM D5185m >4	0	2	---
Titanium	ppm	ASTM D5185m	3	<1	---
Silver	ppm	ASTM D5185m >3	<1	2	---
Aluminum	ppm	ASTM D5185m >20	1	4	---
Lead	ppm	ASTM D5185m >40	2	0	---
Copper	ppm	ASTM D5185m >330	3	418	---
Tin	ppm	ASTM D5185m >15	1	0	---
Antimony	ppm	ASTM D5185m	---	2	---
Vanadium	ppm	ASTM D5185m	<1	0	---
Cadmium	ppm	ASTM D5185m	<1	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 2	6	5	---
Barium	ppm	ASTM D5185m 0	0	<1	---
Molybdenum	ppm	ASTM D5185m 50	52	62	---
Manganese	ppm	ASTM D5185m 0	<1	1	---
Magnesium	ppm	ASTM D5185m 950	871	1053	---
Calcium	ppm	ASTM D5185m 1050	1100	1129	---
Phosphorus	ppm	ASTM D5185m 995	1020	1023	---
Zinc	ppm	ASTM D5185m 1180	1156	1214	---
Sulfur	ppm	ASTM D5185m 2600	3666	2504	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	3	5	---
Sodium	ppm	ASTM D5185m	3	5	---
Potassium	ppm	ASTM D5185m >20	2	5	---



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.2	0.6	---
Nitration	Abs/cm	*ASTM D7624 >20	5.7	8.6	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	17.3	19.6	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	13.2	15.4	---
Base Number (BN)	mg KOH/g	ASTM D2896	9.3	---	---









OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	12.00	11.3	10.9	---

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : PCA0099006 **Received** : 14 Mar 2024
Lab Number : **06118089** **Tested** : 15 Mar 2024
Unique Number : 10926922 **Diagnosed** : 15 Mar 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

MILLER TRUCK LEASING #112
 1504 MAINLINE DR
 CINNAMINSON, NJ
 US 08077
 Contact: MIKE BOYER
 mboyer@millertransgroup.com
 T: (856)662-4264
 F: (856)663-4898

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)