


# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**2126985**

Component  
**Rear Differential**

Fluid  
**PETRO CANADA TRAXON SYNTHETIC 75W90 (--- QTS)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The condition of the oil is acceptable for the time in service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>PCA0114112</b>	PCA0107406	PCA0100732
Sample Date	Client Info		<b>02 Jan 2024</b>	23 Sep 2023	27 Jun 2023
Machine Age	mls	Client Info	<b>56917</b>	35098	0
Oil Age	mls	Client Info	<b>56917</b>	35098	16950
Oil Changed	Client Info		<b>Not Chngd</b>	Not Chngd	Not Chngd
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Water	WC Method	>.2	<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >500	<b>365</b>	346	293
Chromium	ppm	ASTM D5185m >10	<b>3</b>	3	3
Nickel	ppm	ASTM D5185m >10	<b>16</b>	16	12
Titanium	ppm	ASTM D5185m	<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >25	<b>10</b>	10	8
Lead	ppm	ASTM D5185m >25	<b>0</b>	0	0
Copper	ppm	ASTM D5185m >100	<b>4</b>	2	2
Tin	ppm	ASTM D5185m >10	<b>1</b>	2	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 328	<b>119</b>	111	147
Barium	ppm	ASTM D5185m 1	<b>0</b>	0	0
Molybdenum	ppm	ASTM D5185m	<b>3</b>	4	4
Manganese	ppm	ASTM D5185m	<b>16</b>	16	16
Magnesium	ppm	ASTM D5185m 1	<b>0</b>	0	5
Calcium	ppm	ASTM D5185m 7	<b>21</b>	20	29
Phosphorus	ppm	ASTM D5185m 1145	<b>1051</b>	989	1123
Zinc	ppm	ASTM D5185m 3	<b>44</b>	49	65
Sulfur	ppm	ASTM D5185m 17909	<b>27231</b>	24274	27766


## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >75	<b>61</b>	64	66
Sodium	ppm	ASTM D5185m	<b>11</b>	10	11
Potassium	ppm	ASTM D5185m >20	<b>6</b>	9	5

## VISUAL

	method	limit/base	current	history1	history2
White Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Yellow Metal	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Precipitate	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Silt	scalar	*Visual NONE	<b>LIGHT</b>	LIGHT	LIGHT
Debris	scalar	*Visual NONE	<b>NONE</b>	NONE	LIGHT
Sand/Dirt	scalar	*Visual NONE	<b>NONE</b>	NONE	NONE
Appearance	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Odor	scalar	*Visual NORML	<b>NORML</b>	NORML	NORML
Emulsified Water	scalar	*Visual >.2	<b>NEG</b>	NEG	NEG
Free Water	scalar	*Visual	<b>NEG</b>	NEG	NEG

# OIL ANALYSIS REPORT






## FLUID PROPERTIES

method	limit/base	current	history1	history2	
Visc @ 40°C	cSt ASTM D445	99.6	<b>97.0</b>	95.5	96.5

## SAMPLE IMAGES

method	limit/base	current	history1	history2	
Color			no image	no image	no image
Bottom			no image	no image	no image

## GRAPHS



Certificate L2367

**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : PCA0114112      **Received** : 14 Mar 2024  
**Lab Number** : **06118682**      **Tested** : 15 Mar 2024  
**Unique Number** : 10927515      **Diagnosed** : 18 Mar 2024 - Don Baldrige  
**Test Package** : FLEET

**PERDUE FARMS - GEORGETOWN**  
 20621 SAVANAH RD  
 GEORGETOWN, DE  
 US 19947  
 Contact: ROBERT LOCKWOOD  
 Robert.Lockwood@Perdue.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:  
F: